

Cable feed-through plates - MH-27-MULTI-65-PV-BK - 1424583

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable feed-through plates, no. of conductors: 27, external cable diameter: 26x 3 mm ... 6 mm, 1x 10 mm ... 20 mm, material: PP (Core), material: TPE-SEBS (external material), color: black, length: 154 mm, width: 56 mm, height: 18.5 mm

Your advantages

- ✓ The panel cutouts of size B24 heavy-duty connectors can be used.



Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 374864
GTIN	4055626374864

Technical data

Dimensions

Length	154 mm
Width	56 mm
Height	18.5 mm
Drill hole distance, horizontal	130 mm
Drill hole distance, vertical	32 mm
External cable diameter	26x 3 mm ... 6 mm
	1x 10 mm ... 20 mm

Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 90 °C

General

Note	incl. mounting screws
No. of conductors	27
Tightening torque	1.8 Nm

Technical data

Material	TPE-SEBS
	PP (Core)
	TPE-SEBS (external material)
Flammability rating according to UL 94	V0
Color	black
Assembly note	M4 mounting screw, torque: 1.8 Nm, SW5 Allen key
	The mounting screws included should be used for assembly. Assembly steps: 1) Fix Multigates with the mounting screws provided (observe torque) 2) Make a hole in the membrane (with a screwdriver) or cut off the tip of the cone 3) Guide the cable through the opening (from the outside). Withdraw the cable approximately 20 mm (to improve strain relief).

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Technical drawing of a rectangular plate. The top view shows a rectangle with a width of 18.5 and a height of 9. The side view shows a rectangle with a width of 154 and a height of 9. The front view shows a rectangle with a width of 130 and a height of 56. The front view also shows a pattern of holes: a central row of 10 holes with a diameter of $\phi 4$, and two side rows of 5 holes each, also with a diameter of $\phi 4$. The distance between the center of the leftmost hole and the left edge is 11.4. The distance between the center of the rightmost hole and the right edge is 11.4. The distance between the center of the first hole and the center of the last hole in the central row is 79.8. The distance between the center of the first hole and the center of the last hole in the side rows is 34.2. The distance between the center of the first hole and the center of the last hole in the side rows is 11.4. The distance between the center of the first hole and the center of the last hole in the side rows is 11.4.

Technical drawing of a rectangular plate with the following dimensions and features:

- Overall width: 130
- Overall height: 32
- Inner width (excluding hole): 113
- Inner height (excluding hole): 35
- Hole diameter: $\varnothing 4,5$

Classifications

eCl@ss 10.0.1	27400569
eCl@ss 11.0	27400569
eCl@ss 5.1	23110102
eCl@ss 6.0	27409200
eCl@ss 7.0	27409208
eCl@ss 9.0	27400569

Cable feed-through plates - MH-27-MULTI-65-PV-BK - 1424583

Classifications

ETIM

ETIM 6.0	EC001004
ETIM 7.0	EC001004

UNSPSC

UNSPSC 21.0	31163000
-------------	----------

Approvals

Approvals

Approvals

EAC-RoHS / EAC

Ex Approvals

Approval details

EAC-RoHS		RU D- DE.HB35.B.00387
----------	---	--------------------------

EAC		EAC-Zulassung
-----	---	---------------

Phoenix Contact 2022 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)