

Screwdriver - SZS 1,0X4,0 - 1205066

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Screwdriver, bladed, VDE insulated, size: 1.0 x 4.0 x 100 mm, 2-component grip, with non-slip grip

The illustration shows version
SZS 0,6 x 3,5

Why buy this product

- ✓ The tools feature ergonomic two-component safety handles
- ✓ Large contact surface of blades inside screw head
- ✓ Individually tested safety screwdrivers according to DIN EN 60900 (VDE 0682-201)
- ✓ For working on or in the vicinity of live parts up to 1000 V AC or 1500 V DC

Key commercial data

Packing unit	1
Minimum order quantity	10
Catalog page	Page 283 (CL2-2011)
GTIN	 4 017918 019105
Custom tariff number	82054000
Country of origin	CZECH REPUBLIC

Technical data

General

Length (b)	198 mm
Width (a)	33 mm
Design	Phillips
Blade thickness	1 mm
Blade width	4 mm
Blade height	100 mm
Weight	55 g
Test standard	DIN/ISO 2380-1 IEC 60900:2004

Classifications

eclass

eCl@ss 4.0	21040401
------------	----------

Screwdriver - SZS 1,0X4,0 - 1205066

Classifications

eclass

eCl@ss 4.1	21040401
eCl@ss 5.0	21040401
eCl@ss 5.1	21040401
eCl@ss 6.0	21040401
eCl@ss 7.0	21040409

etim

ETIM 2.0	EC000158
ETIM 3.0	EC000158
ETIM 4.0	EC000158

unspsc

UNSPSC 6.01	27111701
UNSPSC 7.0901	27111701
UNSPSC 11	27111701
UNSPSC 12.01	27111701
UNSPSC 13.2	27111701

Approvals

Approvals

Approvals

VDE approval of drawings / GOST / VDE approval of drawings

Ex Approvals

Approvals submitted

Approval details

VDE approval of drawings 

GOST 

Screwdriver - SZS 1,0X4,0 - 1205066

Approvals


VDE approval of drawings 

Drawings

Pictogram



Dimensioned drawing



单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)