

## Cable protection end sleeve - WP-SC PA HF 10,0 BK - 3240981

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



End sleeves as cable protection

### Key Commercial Data

Packing unit	1 STK
Minimum order quantity	50 STK
Custom tariff number	39174000
Country of origin	Germany

### Technical data

#### Dimensions

Length (b)	20 mm
Inner diameter (f)	4.30 mm
Outside diameter	10.00 mm

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 115 °C
---------------------------------	-------------------

#### General

Color	black
Components	Halogen-free
Flammability rating according to UL 94	V0
Material	PA

#### Standards and Regulations

Connection in acc. with standard	UL
Flammability rating according to UL 94	V0

# Cable protection end sleeve - WP-SC PA HF 10,0 BK - 3240981

## Classifications

### eCl@ss

eCl@ss 4.0	27141131
eCl@ss 4.1	27141131
eCl@ss 5.0	27141131
eCl@ss 5.1	27141120
eCl@ss 6.0	27141120
eCl@ss 7.0	27141120
eCl@ss 8.0	27439210

### ETIM

ETIM 3.0	EC000897
ETIM 4.0	EC002584
ETIM 5.0	EC000519

### UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121410
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121411

## Approvals

### Approvals

---

Approvals

UL Recognized / LR

---

Ex Approvals

---

Approvals submitted

---

### Approval details

UL Recognized 
---

## Cable protection end sleeve - WP-SC PA HF 10,0 BK - 3240981

### Approvals

LR

Phoenix Contact 2016 © - all rights reserved  
<http://www.phoenixcontact.com>

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)