

# EMC housing - HC-B 10-TMB-100/O1STM32G-EMV - 1604337

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)

HEAVYCON ADVANCE EMV sleeve housing B10, with bayonet locking, height 100 mm, with 1x M32 thread, straight cable outlet





## Key commercial data

Packing unit	1 PCE
Weight per Piece (excluding packing)	341.26 GRM
Custom tariff number	85389099
Country of origin	Germany

## Technical data

### Dimensions

Height	100 mm
Width	57 mm
Length	105 mm
Length of the assembly cutout	65 mm
Width of the assembly cutout	35 mm

### Ambient conditions

Degree of protection of housing (IP)	IP65
	IP67
Ambient temperature (operation)	-40 °C 125 °C

### General

Note	For contact inserts HC-B10, BB18, DD42, M, K8/24
Design	B10
Housing type	Sleeve housings
Locking type	Bayonet locking
Cable exit	Straight



# EMC housing - HC-B 10-TMB-100/O1STM32G-EMV - 1604337

## Technical data

### General

Screw connection	None
Type of the screw connection	1x M32
Housing material	Aluminum die-cast
Housing surface material	EMC coating, silver
Seal material	NBR, conductive
Material lock	High-grade steel
Material grip body interlock	PA-GF
Assembly instructions	In order to guarantee that the ground conductor contact functions even when plugged in at an angle, the two panel mounting flanges must have sufficient electrical contact with the metal mounting panel.
Connection	If insulating powder coating is present on the control cabinet panel, it should be removed from the profile gasket area in order to ensure optimum shielding.

## Classifications

### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27371205
eCl@ss 7.0	27371205
eCl@ss 8.0	27371205

### ETIM

ETIM 2.0	EC000437
ETIM 3.0	EC000437
ETIM 4.0	EC000437
ETIM 5.0	EC000437

### UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502



# EMC housing - HC-B 10-TMB-100/O1STM32G-EMV - 1604337

### Accessories

Accessories

Panel mounting flange

Mounting flange - HC-B-BF - 1604641



Panel mounting flange for HEAVYCON ADVANCE TMB housing with bayonet locking

Mounting flange - HC-B-BF-SET - 1604654



Bayonet mounting flange set, consisting of 2 mounting flanges with 4 self-tapping Torx® head screws and 4 fan-type spacers


#### Protective cover

Protective covers - HC-B 10-TMB-SD-IP65 - 1690943




HEAVYCON ADVANCE IP65 protective cover B10, with bayonet locking, with retaining cord, diameter of retaining cord eyelet 3 mm

### Drawings



 $\label{eq:panel} \mbox{Panel cutout} $$^2$ When self-tapping screws are used (Torx <math display="inline">\mbox{\ensuremath{\mathbb S}} 20,\,\mbox{\ensuremath{\mathbb M}} 4)$ 

#### Dimensioned drawing





12/6/13 Page 3 / 4



© Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com

12/6/13 Page 4 / 4

>>Phoenix Contact(菲尼克斯)