

Extension module - PSR-SPP- 24UC/URM/3X1/3X2 - 2981842

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Universal safety relay positively driven contact, 3 N/O contacts, 3 N/C contacts, plug-in terminal blocks with spring-cage connection, width: 22.5 mm

The figure shows a version with a screw connection

Product Features

- ✓ Like all PSR safety relays, equipped with forcibly guided contacts according to EN 50205
- ✓ Single-channel control



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	160.0 GRM
Custom tariff number	85364900
Country of origin	Germany

Technical data

Dimensions

Width	22.5 mm
Height	112 mm
Depth	114.5 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 55 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C

Input data

Nominal input voltage U_N	24 V AC/DC
Input voltage range in reference to U_N	0.85 ... 1.1
Typical input current at U_N	45 mA

Extension module - PSR-SPP- 24UC/URM/3X1/3X2 - 2981842

Technical data

Input data

Typical response time	15 ms
Typical release time	15 ms
Status display	Green LED

Output data

Contact type	3 N/O contacts
	3 N/C contacts
Contact material	AgSnO ₂
Minimum switching voltage	15 V AC/DC
Maximum switching voltage	250 V AC/DC
Limiting continuous current	6 A (N/O contact)
	6 A (N/C contact)
Inrush current, minimum	25 mA
Maximum inrush current	6 A
Sq. Total current	$48 \text{ A}^2 (I_{TH}^2 = I_1^2 + I_2^2 + \dots + I_N^2)$
Interrupting rating (ohmic load) max.	144 W (24 V DC, $\tau = 0 \text{ ms}$)
	288 W (48 V DC, $\tau = 0 \text{ ms}$)
	77 W (110 V DC, $\tau = 0 \text{ ms}$)
	88 W (220 V DC, $\tau = 0 \text{ ms}$)
	1500 VA (250 V AC, $\tau = 0 \text{ ms}$)
Maximum interrupting rating (inductive load)	24 V DC, $\tau = 40 \text{ ms}$
	48 V DC, $\tau = 40 \text{ ms}$
	110 V DC, $\tau = 40 \text{ ms}$
	220 V DC, $\tau = 40 \text{ ms}$
Switching capacity min.	0.4 W
Output fuse	10 A gL/gG NEOZED (N/O contact)
	4 A gL/gG NEOZED (N/C contact)

General

Relay type	Electromechanically forcibly guided, dust-proof relay.
Mechanical service life	Approx. 10^7 cycles
Mounting type	DIN rail mounting
Degree of protection	IP20
Min. degree of protection of inst. location	IP54
Mounting position	any
Designation	Air and creepage distances between the power circuits
Standards/regulations	DIN EN 50178/VDE 0160

Extension module - PSR-SPP- 24UC/URM/3X1/3X2 - 2981842

Technical data

General

Rated surge voltage / insulation	4 kV / Basic isolation (safe isolation, reinforced insulation and 6 kV between the input circuit and the output (13/14, 23/24, 33/34).)
Rated insulation voltage	250 V
Pollution degree	2
Surge voltage category	III

Connection data

Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	1.5 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	1.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	16
Stripping length	8 mm
Connection method	Spring-cage connection

Classifications

eCl@ss

eCl@ss 4.0	27371102
eCl@ss 4.1	27371102
eCl@ss 5.0	27371901
eCl@ss 5.1	27371901
eCl@ss 6.0	27371819
eCl@ss 7.0	27371819
eCl@ss 8.0	27371819

ETIM

ETIM 2.0	EC001449
ETIM 3.0	EC001449
ETIM 4.0	EC001449
ETIM 5.0	EC001449

UNSPSC

UNSPSC 6.01	30211901
UNSPSC 7.0901	39121501
UNSPSC 11	39121501
UNSPSC 12.01	39121501
UNSPSC 13.2	39121501

Extension module - PSR-SPP- 24UC/URM/3X1/3X2 - 2981842

Approvals

Approvals

Approvals

UL Listed / GOST / cUL Listed / cULus Listed

Ex Approvals

Approvals submitted

Approval details

UL Listed 


GOST 

cUL Listed 

cULus Listed 

Drawings

Circuit diagram



单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)