

## Connector - C-SCFI 2,5/4,8X0,8 - 3240054

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Slip-on sleeve, blue, 1.5 - 2.5 mm², 4.8 x 0.8

### Product Features

- ✓ Electrolytic tin plating
- ✓ Hard-soldered crimping zone for maximum pull-out forces
- ✓ Halogen-free
- ✓ 'EASY ENTRY' for easy and reliable conductor entry



### Key commercial data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 1      |
| Minimum order quantity               | 100 1    |
| Weight per Piece (excluding packing) | 0.2 GRM  |
| Custom tariff number                 | 85366990 |
| Country of origin                    | China    |

### Technical data

#### Dimensions

|                                              |        |
|----------------------------------------------|--------|
| Length (b)                                   | 20 mm  |
| Width (a)                                    | 4.8 mm |
| Length of insulation sleeve (c)              | 11 mm  |
| Inner dimension of the insulating collar (d) | 5 mm   |
| Material thickness (g)                       | 0.4 mm |

#### Ambient conditions

|                                 |                   |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -20 °C ... 105 °C |
|---------------------------------|-------------------|

#### General

|       |      |
|-------|------|
| Color | blue |
|-------|------|

## Connector - C-SCFI 2,5/4,8X0,8 - 3240054

### Technical data

#### General

|                  |              |
|------------------|--------------|
| Stripping length | 8 mm         |
| Components       | Halogen-free |
| Material         | Brass        |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27060701 |
| eCl@ss 4.1 | 27060701 |
| eCl@ss 5.0 | 27400201 |
| eCl@ss 5.1 | 27400201 |
| eCl@ss 6.0 | 27400201 |
| eCl@ss 7.0 | 27400201 |
| eCl@ss 8.0 | 27400201 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000005 |
| ETIM 3.0 | EC000005 |
| ETIM 4.0 | EC001052 |
| ETIM 5.0 | EC001052 |


#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211923 |
| UNSPSC 7.0901 | 27121703 |
| UNSPSC 11     | 27121703 |
| UNSPSC 12.01  | 27121703 |
| UNSPSC 13.2   | 27121703 |

### Drawings

## Connector - C-SCFI 2,5/4,8X0,8 - 3240054

Dimensioned drawing



单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)