

Operator terminal - NLC-OP2-LCD-076-4X20 - 2701945

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Remote user interface for Nanoline controllers. RS-232 interface allows mounting up to 15 m away.



Product Features

- ✓ Numeric (0 - 9), direction (up, down, left, right), and Enter keys can be used to input custom messages
- ✓ Displays messages prompting user input
- ✓ The hot-swappable design enables use as a service tool and for security
- ✓ Provides access to view all I/O points, registers, flags, timers, counters, program flags, and system flags

Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	400.0 GRM
Country of origin	India

Technical data

Dimensions

Width	128 mm
Height	102 mm
Depth	44.5 mm

Ambient conditions

Degree of protection	IP66
Ambient temperature (operation)	0 °C ... 50 °C
Ambient temperature (storage/transport)	0 °C ... 60 °C

Supply

Power supply connection	3-pos. Combicon
Supply voltage	24 V DC
Supply voltage range	10.8 V DC ... 26.4 V DC
Max. current consumption	40 mA (24 V DC)
Typical current consumption	38 mA (24 V DC)

Operator terminal - NLC-OP2-LCD-076-4X20 - 2701945

Technical data

Software interfaces

Programming tool	nanoNavigator
------------------	---------------

General

Mounting type	Panel mounting
---------------	----------------

Classifications

eCl@ss

eCl@ss 5.1	27249290
eCl@ss 8.0	27242216

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)