

## Printed-circuit board connector - BCH-350VF- 4 - 5431013

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 4, Pitch: 3.5 mm, Color: Signal gray, Contact surface: Tin, Assembly: Soldering



The illustration shows the 5-position version of the product



### Key commercial data

|                        |                                                                                                         |
|------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit           | 1 PCE                                                                                                   |
| Minimum order quantity | 100 PCE                                                                                                 |
| GTIN                   | <br>4 046356 492898 |
| Custom tariff number   | 85366990                                                                                                |
| Country of origin      | CHINA                                                                                                   |

### Technical data

#### Dimensions

|                |              |
|----------------|--------------|
| Length         | 7.4 mm       |
| Pitch          | 3.5 mm       |
| Dimension a    | 10.5 mm      |
| Pin dimensions | 0,8 x 0,8 mm |
| Hole diameter  | 1.2 mm       |

#### General

|                             |        |
|-----------------------------|--------|
| Range of articles           | BCH-VF |
| Insulating material group   | I      |
| Rated surge voltage (III/3) | 2.5 kV |
| Rated surge voltage (III/2) | 2.5 kV |
| Rated surge voltage (II/2)  | 2.5 kV |

# Printed-circuit board connector - BCH-350VF- 4 - 5431013

## Technical data

### General

|                                         |             |
|-----------------------------------------|-------------|
| Rated voltage (III/3)                   | 160 V       |
| Rated voltage (III/2)                   | 160 V       |
| Rated voltage (II/2)                    | 320 V       |
| Connection in acc. with standard        | EN-VDE      |
| Nominal current $I_N$                   | 8 A         |
| Maximum load current                    | 8 A         |
| Insulating material                     | PA          |
| Inflammability class according to UL 94 | V0          |
| Color                                   | Signal gray |
| Nominal voltage, UL/CUL Use Group B     | 250 V       |
| Nominal current, UL/CUL Use Group B     | 8 A         |
| Nominal voltage, UL/CUL Use Group D     | 300 V       |
| Nominal current, UL/CUL Use Group D     | 8 A         |
| Number of positions                     | 4           |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27261101 |
| eCl@ss 7.0 | 27440401 |

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002637 |
| ETIM 5.0 | EC002637 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211801 |
| UNSPSC 7.0901 | 39121432 |
| UNSPSC 11     | 39121432 |
| UNSPSC 12.01  | 39121409 |
| UNSPSC 13.2   | 39121432 |

## Printed-circuit board connector - BCH-350VF- 4 - 5431013

### Approvals

#### Approvals

---

#### Approvals

UL Recognized / cUL Recognized / cULus Recognized

---

#### Ex Approvals

---

#### Approvals submitted

---

#### Approval details

|                                                                                                  |       |       |
|--------------------------------------------------------------------------------------------------|-------|-------|
| UL Recognized  |       |       |
|                                                                                                  | B     | D     |
| Nominal current I <sub>N</sub>                                                                   | 8 A   | 8 A   |
| Nominal voltage U <sub>N</sub>                                                                   | 250 V | 300 V |

|                                                                                                    |       |       |
|----------------------------------------------------------------------------------------------------|-------|-------|
| cUL Recognized  |       |       |
|                                                                                                    | B     | D     |
| Nominal current I <sub>N</sub>                                                                     | 8 A   | 8 A   |
| Nominal voltage U <sub>N</sub>                                                                     | 250 V | 300 V |

|                                                                                                      |  |  |
|------------------------------------------------------------------------------------------------------|--|--|
| cULus Recognized  |  |  |
|------------------------------------------------------------------------------------------------------|--|--|

### Accessories

#### Accessories

#### Marking

## Printed-circuit board connector - BCH-350VF- 4 - 5431013

### Accessories

Marker pen - B-STIFT - 1051993



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm

---

Marker cards - SK 3,5/2,8:FORTL.ZAHLEN - 0804073



Marker cards, Card, white, labeled, Horizontal: Consecutive numbers 1 - 10, 11 - 20, etc. up to 91 - 99, Mounting type: Adhesive, For terminal block width: 3.5 mm

---

Marker cards - SK U/2,8 WH:UNBEDRUCKT - 0803883



Marker cards, Sheet, white, Unlabeled, Can be labeled with: Plotter, Office printing systems, Mounting type: Adhesive, Lettering field: 186 x 2.8 mm

---

Coding profile - CP-BC-M - 5436160




Coding profile

---

### Drawings

## Printed-circuit board connector - BCH-350VF- 4 - 5431013

Dimensioned drawing





单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)