

Antenna - RAD-ISM-2400-ANT-OMNI-5-0 - 2884923

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Omni-directional antenna, degree of protection IP55, 5 dBi gain, linear vertical, SMA (male), impedance 50 ohms, apex angle h/v 360°/45°

Product Features

- ✓ For mobile applications with a longer range

Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	37.9 g
Custom tariff number	85177019
Country of origin	Taiwan

Technical data

Dimensions

Width	13 mm
Height	187 mm

Ambient conditions

Degree of protection	IP55
Ambient temperature (operation)	-20 °C ... 65 °C
Ambient temperature (storage/transport)	-20 °C ... 65 °C

General

With connecting cable	No
Frequency range	2.4 GHz
	2.4 GHz
Horizontal beamwidth	360 °
Vertical beamwidth	45 °
Impedance	50 Ω
Gain	5 dBi

Antenna - RAD-ISM-2400-ANT-OMNI-5-0 - 2884923

Technical data

General

Connection method	SMA (male)
-------------------	------------

Classifications

eCl@ss

eCl@ss 4.0	27240409
eCl@ss 4.1	27240409
eCl@ss 5.0	27242215
eCl@ss 5.1	19070102
eCl@ss 6.0	27242208
eCl@ss 7.0	27242208
eCl@ss 8.0	19070105

ETIM

ETIM 2.0	EC001423
ETIM 3.0	EC001423
ETIM 4.0	EC001423
ETIM 5.0	EC001698

UNSPSC

UNSPSC 6.01	20142601
UNSPSC 7.0901	20142601
UNSPSC 11	20142601
UNSPSC 12.01	20142601
UNSPSC 13.2	20142601

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)