

## Energy storage - QUINT-BAT/24DC/ 7.2AH - 2866352

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Energy storage device, lead AGM, VRLA technology, 24 V DC, 7.2 Ah. Connection via pin cable lug, 14 mm.



### Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	7194.6 g
Custom tariff number	85072080
Country of origin	China

### Technical data

#### Dimensions

Width	164 mm
Height	156 mm
Depth	110 mm

#### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 40 °C
Ambient temperature (storage/transport)	0 °C ... 40 °C

#### Input data

Nominal input voltage	24 V DC
-----------------------	---------

#### Output data

Nominal output voltage	24 V DC
Output current $I_{max}$	50 A
Connection in parallel	Yes, for increasing the buffer period
Connection in series	No

# Energy storage - QUINT-BAT/24DC/ 7.2AH - 2866352

## Technical data

### Output data

Output fuse	2x 25 A
-------------	---------

### General


IQ technology	No
Net weight	6 kg
Memory medium	battery 7.2 Ah
Protection class	III

### Standards and Regulations

Shipbuilding approval	Germanischer Lloyd (EMC 2), ABS
-----------------------	---------------------------------

## Drawings

Block diagram



## Classifications

### eCl@ss

eCl@ss 4.0	27040603
eCl@ss 4.1	27040603
eCl@ss 5.0	27040603
eCl@ss 5.1	27040603
eCl@ss 6.0	27040603
eCl@ss 7.0	27049201
eCl@ss 8.0	27050403
eCl@ss 9.0	27050403

### ETIM

ETIM 2.0	EC000382
ETIM 3.0	EC000382
ETIM 4.0	EC000357
ETIM 5.0	EC000357

# Energy storage - QUINT-BAT/24DC/ 7.2AH - 2866352

## Classifications

### UNSPSC

UNSPSC 6.01	30211510
UNSPSC 7.0901	39121011
UNSPSC 11	39121011
UNSPSC 12.01	39121011
UNSPSC 13.2	39121011

## Approvals

### Approvals

---

#### Approvals

GL / EAC / EAC / DNV / ABS / ABS

---

#### Ex Approvals

---

#### Approvals submitted

---

## Approval details

GL

EAC

EAC

DNV

ABS

ABS

## Accessories

### Accessories

Assembly adapter

## Energy storage - QUINT-BAT/24DC/ 7.2AH - 2866352

### Accessories

Assembly adapters - QUINT-ADAPTER/4 - 2866857

Assembly adapter for QUINT-BAT/24DC... on 35mm rail



---

### Fuse

Fuse - SI FORM C 25 A DIN 72581 - 0913757



Flat-type plug-in fuse, type C, color code: white, nominal current: 25 A

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact \(菲尼克斯\)](#)