

Safety label with special adhesive - EMLS (70X32)R SR - 0800346

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Safety label with special adhesive, Roll, silver, unlabeled, can be labeled with: THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK X1.2, Mounting type: Adhesive, Lettering field: 70 x 32 mm

The figure shows a version of the article

Product Features

- Labeling service: Phoenix Contact can custom-label all EMLS ... markers according to your requirements
- The safety function is ensured up to 80°C
- The EMLS ... materials are UL-listed
- Tamper-proof label, can be used as a rating plate or seal, for example
- When peeled off, part of the metallic layer comes away, leaving behind a triangular pattern on both the label and the surface

Key Commercial Data

| | |
|--------------------------------------|----------|
| Packing unit | 1 pc |
| Weight per Piece (excluding packing) | 360.0 g |
| Custom tariff number | 39199000 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|------------|-------|
| Length (b) | 70 mm |
| Width (a) | 32 mm |

Ambient conditions

| | |
|---------------------------------|---|
| Ambient temperature (operation) | -40 °C ... 150 °C |
| Ambient temperature (assembly) | > 5 °C |
| Recommended storage conditions | 10-25 °C / 35-65 % relative humidity. Storage in a cool and dry place is recommended. |

General

| | |
|------------|--------------------------------|
| Color | silver |
| Components | free from silicone and halogen |

Safety label with special adhesive - EMLS (70X32)R SR - 0800346

Technical data

General

| | |
|---|-------------------------------------|
| Material | Polyester |
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Number of individual labels | 500 |
| Number of individual labels per row | 1 |
| RoHS compliant | Yes |
| Adhesive | Acrylic |
| File number | UL-MH48542 / PC-014 |
| Printability | Thermal transfer |
| Device | 5146477 THERMOMARK ROLL |
| | 5146723 THERMOMARK ROLL X1 |
| | 5146257 THERMOMARK S1.1 |
| | 5146231 THERMOMARK X1.2 |
| Ink ribbon | 5145384 THERMOMARK-RIBBON 110 |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02 |
| Result | Test passed |
| Test specification weathering-resistance | Following ISO 4892-2:2013-03 |
| Test duration | 96 h |
| Wipe resistance test result | Test passed |
| Salt spray test specification | DIN EN 60068-2-11:2000-02 |
| Test duration | 96 h |
| Salt spray testing result | Test passed |
| Alternating condensation climate with SO2 test specification | Following DIN 50018:2013-05 |
| Climate level | AHT 1.0 S |
| Cycles | 2 |
| Condensation test result | Test passed |
| Wipe resistance of test specification inscriptions | DIN EN 61010-1 (VDE 0411-1):2011-07 |
| Result | Test passed |
| Foil strength | 53 µm |
| Adhesive strength | 20 µm |
| Marking mounting type | Adhesive |

Standards and Regulations

| | |
|----------------------------------|-----------------------------|
| Connection in acc. with standard | UL |
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |

Safety label with special adhesive - EMLS (70X32)R SR - 0800346

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 24190219 |
| eCl@ss 4.1 | 24190219 |
| eCl@ss 5.0 | 27149103 |
| eCl@ss 5.1 | 27141137 |
| eCl@ss 6.0 | 27141137 |
| eCl@ss 7.0 | 27141137 |
| eCl@ss 8.0 | 27149129 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 5.0 | EC001288 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 39121410 |

Approvals

Approvals

Approvals

UL Recognized

Ex Approvals

Approvals submitted

Approval details

| |
|---------------|
| UL Recognized |
|---------------|

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)