

## Adapter module - IFS-OP-CRADLE - 2811886

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



The adapter (IFS-OP-CRADLE) for the operator interface is ideal for use as a remote operator panel and display device for 17.5 mm/35 mm modules. Can be mounted directly on the DIN rail.

### Product Features

- ✓ For snapping onto the DIN rail
- ✓ For control cabinet mounting of the operating and display unit



### Key commercial data

|                                      |           |
|--------------------------------------|-----------|
| Packing unit                         | 1 PCE     |
| Weight per Piece (excluding packing) | 100.0 GRM |
| Custom tariff number                 | 85444290  |
| Country of origin                    | Germany   |

### Technical data

#### Note:

|                         |                                                                           |
|-------------------------|---------------------------------------------------------------------------|
| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
|-------------------------|---------------------------------------------------------------------------|

### Dimensions

|        |         |
|--------|---------|
| Width  | 35.2 mm |
| Height | 29 mm   |
| Depth  | 99 mm   |

### Ambient conditions

|                                         |                                   |
|-----------------------------------------|-----------------------------------|
| Ambient temperature (operation)         | -20 °C ... 65 °C (-4°F ... 149°F) |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C (-40°F...185°F)  |
| Maximum altitude                        | ≤ 2000 m                          |

# Adapter module - IFS-OP-CRADLE - 2811886

## Technical data

### Ambient conditions

|                                  |                                  |
|----------------------------------|----------------------------------|
| Permissible humidity (operation) | 90 % (at 25 °C, no condensation) |
| Noise immunity                   | EN 61000-6-2                     |

### General

|                               |                                            |
|-------------------------------|--------------------------------------------|
| Electromagnetic compatibility | Conformance with EMC Directive 2004/108/EC |
| Emitted interference          | EN 61000-6-4                               |
| Housing material              | PA 6.6                                     |
| Conformance                   | CE-compliant                               |
| ATEX                          | # II 3G Ex nA ic IIC T4 Gc X               |
| IECEX                         | Ex nA ic IIC T4 X                          |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27210120 |
| eCl@ss 4.1 | 27210120 |
| eCl@ss 5.0 | 27210120 |
| eCl@ss 5.1 | 27210120 |
| eCl@ss 6.0 | 27210120 |
| eCl@ss 7.0 | 27210120 |
| eCl@ss 8.0 | 27210120 |

### ETIM

|          |          |
|----------|----------|
| ETIM 4.0 | EC002498 |
| ETIM 5.0 | EC002498 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211920 |
| UNSPSC 7.0901 | 39121519 |
| UNSPSC 11     | 39121519 |
| UNSPSC 12.01  | 39121519 |
| UNSPSC 13.2   | 39121519 |

## Approvals

### Approvals

---

# Adapter module - IFS-OP-CRADLE - 2811886

## Approvals

Approvals

UL Listed / cUL Listed / cULus Listed

Ex Approvals

IECEX / ATEX / IECEX / ATEX

Approvals submitted

### Approval details

UL Listed 

cUL Listed 

cULus Listed 

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)