

Cable gland - G-INS-NPT3/8-S68L-NNES-S - 1411182

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Brass, nickel-plated, External cable diameter 5 mm ... 10 mm, Shielding: No, Connecting thread: NPT3/8 inch, Color: silver



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
Weight per Piece (excluding packing)	24.0 g
Custom tariff number	74199990
Country of origin	Turkey

Technical data

Dimensions

Length	34 mm
Wrench size, union nut	17 mm
Wrench size, support	19 mm
Hexagon angular dimension GRP	22 mm
Length of the connecting thread	11.5 mm
External cable diameter	5 mm ... 10 mm

Ambient conditions

Degree of protection	IP68
	4X
Ambient temperature (operation)	-20 °C ... 100 °C (static)

General

Cable gland material	Brass, nickel-plated
Seal material	Neoprene
Cable seal material	Neoprene

Cable gland - G-INS-NPT3/8-S68L-NNES-S - 1411182

Technical data

General

O-ring material	NBR
Shielded	No
Thread type on connection side	NPT3/8 inch
Torque	8 Nm ... 10 Nm (Union nut)
Color	silver

Standards and Regulations

Connection in acc. with standard	UL
----------------------------------	----

Classifications

eCl@ss

eCl@ss 5.1	27081002
eCl@ss 6.0	27081002
eCl@ss 8.0	27149109

ETIM

ETIM 4.0	EC000441
ETIM 5.0	EC000441

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals


Approvals submitted


Approval details

UL Recognized 

Cable gland - G-INS-NPT3/8-S68L-NNES-S - 1411182


Approvals

cUL Recognized 

cULus Recognized 

Drawings

Dimensional drawing



Dimensional drawing

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)