

https://www.phoenixcontact.com/us/products/1148690



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Web panel with 47.0 cm / 18.5" TFT-display (projective-capacitive (PCAP)), 1366 x 768 pixel(s) (HD), 16.7 million colors, Arm[®] Cortex[®]-A53, 4x 1.2 GHz, 2x USB host 2.0, 1 x Ethernet (10/100 Mbps), RJ45, Yocto/Linux and user software: Chromium Browser. (bus system: without)

Your advantages

- · Easy startup just enter the IP and URL
- · Flexible, thanks to open web standard and free choice of web server and visualization software
- No security updates are required for JAVA or Flash plug-ins thanks to HTML5
- · Ideal for use with PLCnext Engineer or CODESYS
- · Embedded Linux operating system
- · Visualization of self-programmed JavaScript applications possible
- Secure communication, thanks to SSL-encrypted data transmission

Commercial Data

Item number	1148690
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	D16
Product Key	DRCADF
GTIN	4063151142346
Weight per Piece (including packing)	6,660 g
Weight per Piece (excluding packing)	5,000 g
Customs tariff number	84714100
Country of origin	DE



https://www.phoenixcontact.com/us/products/1148690



Technical Data

Product properties

Product type	Operator panel	
Computer data		
Processor	Arm [®] Cortex [®] -A53, 4x 1.2 GHz	
Operating system	Yocto/Linux	
RAM	1 GB LPDDR3	
Data storage	Flash eMMC, 8 GB	
Slots	1x microSD	
Display		
Display type	47.0 cm / 18.5" TFT	
Screen resolution	1366 x 768 Pixel(s) (HD)	
Touch technology	projective-capacitive (PCAP)	
Display lighting type	LED	
Brightness	240 cd/m², typical (adjustable)	
MTBF	50000 h	
Color spectrum	16.7 million colors	
Reading angle left	85 °	
Reading angle right	85 °	
Reading angle top	80 °	
Reading angle bottom	80 °	

Software

User software	Chromium Browser
System requirements	
Runtime system	Chromium browser

Interfaces

Interfaces	2x USB Host 2.0
Optional interfaces	Without optional interface
Network	1 x Ethernet (10/100 Mbps), RJ45
Bus system	without

Electrical properties

Su	pp	ŀ
Su	pp	ľ

Supply voltage	24 V DC
Supply voltage range	18 V 30 V
Power supply unit	24 V DC ±20 %
Typical current consumption	1.2 A

Real-time clock



https://www.phoenixcontact.com/us/products/1148690



Realtime clock	Integrated (battery backup)		
Mounting			
Mounting type	Front mounting		
Material specifications			
Material front plate	Aluminum (natural anodized)		
Housing material	Steel sheet, zinc-plated		
Ambient conditions			
Degree of protection	IP65 (front), IP20 (back)		
Ambient temperature (operation)	0 °C 50 °C		
Ambient temperature (storage/transport)	-20 °C 60 °C		
Altitude	3000 m		
Permissible humidity (operation)	20 % 85 % (non-condensing)		
Permissible humidity (storage/transport)	20 % 85 % (non-condensing)		
Shock	DIN EN 60068-2-27		
Vibration (operation)	DIN EN 60068-2-6		
Dimensions			
External dimensions			
Width / Height / Depth	485 mm / 329 mm / 8 mm (Dimensions of the front plate)		
Installation dimensions			
Width / Height / Installation depth	475 mm / 311 mm / 53 mm (Installation cutout)		



https://www.phoenixcontact.com/us/products/1148690



Approvals



UL Listed

Approval ID: FILE E 238705



cUL Listed

Approval ID: FILE E 238705

cULus Listed



https://www.phoenixcontact.com/us/products/1148690



Classifications

ECLASS

UNSPSC 21.0

	ECLASS-9.0	27330201
	ECLASS-10.0.1	27330201
	ECLASS-11.0	27330201
ETIM		
	ETIM 8.0	EC001412
UN	SPSC	

43211900



https://www.phoenixcontact.com/us/products/1148690



Environmental Product Compliance

REACh SVHC Lead 7439-92-1



https://www.phoenixcontact.com/us/products/1148690



Accessories

USB memory stick

USB memory stick - USB FLASH DRIVE - 2402809 https://www.phoenixcontact.com/us/products/2402809

USB memory stick, 8 GB



Mounting material

Mounting material - HMI SCB MOUNTING KIT 6 - 2701385 https://www.phoenixcontact.com/us/products/2701385



HMI mounting kit for installation on a front plate. The mounting kit includes 6 x mounting brackets, $6 \, x$ screw threads, and a hexagonal wrench.



https://www.phoenixcontact.com/us/products/1148690



PCB connector

PCB connector - MC 1,5/ 3-STF-3,5 BD:1-3 - 1751312 https://www.phoenixcontact.com/us/products/1751312



PCB connector, nominal cross section: 1.5 mm², color: green, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Tin, type of contact: Female connector, number of potentials: 3, number of rows: 1, number of positions: 3, number of connections: 3, product range: MC 1,5/..-STF, pitch: 3.5 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, number of solder pins per potential: 1, plug-in system: COMBICON MC 1,5, locking: Screw locking, mounting: Screw flange, type of packaging: packed in cardboard

Mounting material

Mounting material - HMI WALL MOUNTING KIT - 2701380 https://www.phoenixcontact.com/us/products/2701380

HMI mounting kit for panel installation. The mounting kit includes 2 spring clips.





https://www.phoenixcontact.com/us/products/1148690



Memory

Memory - MICROSDHC-16GB - 1154696 https://www.phoenixcontact.com/us/products/1154696

Industrial grade 16 GB MicroSDHC 3DTLC



Memory

Memory - MICROSDHC-32GB - 1154699 https://www.phoenixcontact.com/us/products/1154699

Industrial grade 32 GB MicroSDHC 3DTLC



Phoenix Contact 2022 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com

单击下面可查看定价,库存,交付和生命周期等信息

>>Phoenix Contact(菲尼克斯)