

Cable gland - VC-M-KV-PG21 2X6/2X8 - 1885635

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Multiple screw connection Pg21, made of metal, consisting of rubber seal with several holes (2 x 6 mm/2 x 8 mm) and a pressure screw, for cable screw connection support VC-M-KV-PG21...



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	31.57 GRM
Custom tariff number	74153300
Country of origin	Poland

Technical data

Dimensions

Wrench size, union nut	30 mm
External cable diameter	5.5 mm ... 6 mm (Cable 1)
	5.5 mm ... 6 mm (Cable 2)
	7.5 mm ... 8 mm (Cable 3)
	7.5 mm ... 8 mm (Cable 4)
Clamping range of the strain relief clip	7.80 mm ... 8.00 mm (2*line B)

Ambient conditions

Degree of protection	IP65
	IP65
Ambient temperature (operation)	-40 °C ... 125 °C

General

Material, pressure screw	Nickel-plated brass
Seal material	TPE
Cable seal material	TPE
Shielded	No

Cable gland - VC-M-KV-PG21 2X6/2X8 - 1885635

Technical data

General

Thread type on seal side	Pg21
Tightening torque, union nut	10.00 Nm

Classifications

eCl@ss

eCl@ss 4.0	27141209
eCl@ss 4.1	27141209
eCl@ss 5.0	27149109
eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 7.0	27149109
eCl@ss 8.0	27149109

ETIM

ETIM 2.0	EC000441
ETIM 3.0	EC000441
ETIM 4.0	EC000441
ETIM 5.0	EC000441

UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502

Approvals

Approvals

Approvals

GOST

Ex Approvals

Cable gland - VC-M-KV-PG21 2X6/2X8 - 1885635

Approvals


Approvals submitted

Approval details



Drawings

Dimensioned drawing



单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)