

# Connector - ES-BPC-C 35 BK



1176270

<https://www.phoenixcontact.com/pc/products/1176270>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



High-voltage connector for new energy storage system, plug, rated voltage: 1500 V DC, rated current: 160 A ( TUV ) /150A ( UL4128 ) ; color: black (negative pole), contact surface: silver / tin; wiring method: crimping

## Your advantages

- Patented design with "three proofs and one rotation"
- Safety lock
- 360° free rotation and flexible wiring
- Foolproof mechanism installed
- Touch-proof
- Mismatching and short circuit proof

## Commercial Data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1176270       |
| Packing unit                         | 15 pc         |
| Minimum order quantity               | 1 pc          |
| Product Key                          | ABLDBA        |
| GTIN                                 | 4063151207557 |
| Weight per Piece (including packing) | 89.2 g        |
| Weight per Piece (excluding packing) | 89.2 g        |
| Customs tariff number                | 85359000      |
| Country of origin                    | CN            |

## Technical Data

### Notes

#### Safety note

##### Safety note

- **WARNING:** Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.
- **WARNING:** Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.
- **WARNING:** The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.
- The products are suitable for applications in plant, controller, and electrical device engineering.
- Assembled products may not be manipulated or improperly opened.
- Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at [phoenixcontact.com/products](https://www.phoenixcontact.com/products)).
- When using the product in direct connection with third-party manufacturers, the user is responsible.
- For operating voltages > 50 V AC, conductive connector housings must be grounded
- Ensure that the protective or functional ground has been properly connected.
- Observe the corresponding technical data. You will find information:
  - o On the product
  - o On the packing label
  - o In the supplied documentation
  - o Online at [phoenixcontact.com/products](https://www.phoenixcontact.com/products) under the product
- The installation notes/Design In documents online on the download page at [phoenixcontact.com/products](https://www.phoenixcontact.com/products) must be observed for this product.
- Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory section of the product at [phoenixcontact.com/products](https://www.phoenixcontact.com/products)
- The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting warnings (e.g. DIN EN ISO 13732-1:2008-12).
- Operate the connector only when it is fully plugged in and interlocked.
- Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.

# Connector - ES-BPC-C 35 BK



1176270

<https://www.phoenixcontact.com/pc/products/1176270>

- Observe the minimum bending radius of the cable. Lay the cable without twisting it.

## Product properties

|              |                               |
|--------------|-------------------------------|
| Product type | Connectors for energy storage |
|--------------|-------------------------------|

## Insulation characteristics

|                     |   |
|---------------------|---|
| Degree of pollution | 2 |
|---------------------|---|

## Electrical properties

|                                |                 |
|--------------------------------|-----------------|
| Rated voltage (III/2)          | 1500 V DC       |
| Rated current                  | 160 A (TUV)     |
|                                | 150 A (UL 4128) |
| Contact resistance             | ≤ 0.5 mΩ        |
| Nominal voltage U <sub>N</sub> | 1500 V          |

## Material specifications

|  |             |
|--|-------------|
| Color                                  | black       |
| Flammability rating according to UL 94 | V0          |
| Seal material                          | Silicon     |
| Insulating material                    | PA          |
| Contact material                       | Cu/Cu alloy |

## Connector

|                             |     |
|-----------------------------|-----|
| Insertion/withdrawal cycles | 100 |
|-----------------------------|-----|

## Cable / line

|              |     |
|--------------|-----|
| Halogen-free | yes |
|--------------|-----|

## Mechanical properties

### Mechanical data

|                  |        |
|------------------|--------|
| Insertion force  | ≤ 75 N |
| Withdrawal force | ≥ 10 N |

## Environmental and real-life conditions

### Ambient conditions

|   |                           |
|---|---------------------------|
| Degree of protection                    | IP65/IP67 (Mating socket) |
| Degree of protection                    | IP65                      |
| Ambient temperature (operation)         | -40 °C ... 125 °C         |
| Ambient temperature (storage/transport) | -40 °C ... 80 °C          |
| Altitude                                | 4000 m                    |

## Mounting

|                       |   |
|-----------------------|---|
| Assembly instructions | We recommend to use the crimping dies and other crimping devices of Jiangsu Bozhiwang Automation Equipment Co.,Ltd. |
|-----------------------|---|

# Connector - ES-BPC-C 35 BK

1176270

<https://www.phoenixcontact.com/pc/products/1176270>



for cable crimp connection; Address: No. 39 Kun Lun Road, Xin Bei District, Changzhou, Jiangsu Province, China, Email: [flacz2020@163.com](mailto:flacz2020@163.com), die model: BZW-6F

# Connector - ES-BPC-C 35 BK

1176270

<https://www.phoenixcontact.com/pc/products/1176270>



## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27440390 |
|-------------|----------|

### ETIM

|          |          |
|----------|----------|
| ETIM 8.0 | EC001121 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# Connector - ES-BPC-C 35 BK



1176270

<https://www.phoenixcontact.com/pc/products/1176270>

## Environmental Product Compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

Phoenix Contact 2022 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)