

Shock protection - EMLPR (80X60) - 0800358

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Shock protection, Roll, transparent, Unlabeled, Mounting type: Adhesive, Lettering field: 80 x 60 mm



The figure shows a similar product

Product Features

- High level of mechanical and chemical stability
- Extremely thick, yet flexible and transparent label made from halogen-free PU
- Suitable for permanent outdoor use
- Stuck over labels or markers that have been labeled to protect them

Key commercial data

| | |
|--------------------------------------|----------|
| Packing unit | 1 PCE |
| Minimum order quantity | 10 PCE |
| Weight per Piece (excluding packing) | 12.0 GRM |
| Custom tariff number | 39199000 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|------------|-------|
| Length (b) | 80 mm |
| Width (a) | 60 mm |

Ambient conditions

| | |
|---------------------------------|------------------------------------|
| Ambient temperature (operation) | -40 °C ... 90 °C |
| Recommended storage conditions | 18-26 °C / 60 % relative humidity. |

General

| | |
|-----------------------------|---------------|
| Color | transparent |
| Components | Halogen-free |
| Material | Urethane foil |
| Number of individual labels | 4 |

Shock protection - EMLPR (80X60) - 0800358

Technical data

General

| | |
|---|------------------------------|
| Number of individual labels per row | 1 |
| Adhesive | Acrylic |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02 |
| Result | Test passed |
| Test specification weathering-resistance | Following ISO 4892-2:2013-03 |
| Test duration | 4000 h |
| Wipe resistance test result | Test passed |
| Alternating condensation climate with SO2 test specification | Following DIN 50018:2013-05 |
| Climate level | AHT 1.0 S |
| Cycles | 2 |
| Condensation test result | Test passed |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 24190219 |
| eCl@ss 4.1 | 24190219 |
| eCl@ss 5.0 | 27149103 |
| eCl@ss 5.1 | 27141137 |
| eCl@ss 6.0 | 27141137 |
| eCl@ss 7.0 | 27141137 |
| eCl@ss 8.0 | 27141137 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 5.0 | EC000761 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 39121410 |

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)