

Sealing cap - PROT-M12 FS-M - 1430488

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




M12 metal sealing cap for unoccupied M12 plugs of the sensor/actuator cable, flush-type plugs and I/O devices in the field

Your advantages

- ✓ Reliable protection of unoccupied slots during transport and use in the field
- ✓ Robust and reliable: brass protective cap up to IP69K degree of protection
- ✓ Protected against splash water and dust by the internal seal
- ✓ Easy assembly by hand or using a wrench



Key Commercial Data

Packing unit	10 pc
GTIN	 4 046356 325776
GTIN	4046356325776

Technical data

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
	-40 °C ... 85 °C
Degree of protection	IP65
	IP67
	IP69K

General

Note	Use up to max. 48 V AC and 60 V DC
------	------------------------------------

Material

Material	CuZn/Ni
Sealing material	NBR

Environmental Product Compliance

Sealing cap - PROT-M12 FS-M - 1430488


Technical data

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Drawings

Dimensional drawing



Classifications

eCl@ss

eCl@ss 10.0.1	23111190
eCl@ss 11.0	23111190
eCl@ss 4.0	27260700
eCl@ss 4.1	27260700
eCl@ss 5.0	27260700
eCl@ss 5.1	27260700
eCl@ss 6.0	27261200
eCl@ss 7.0	27440208
eCl@ss 9.0	23111190

ETIM

ETIM 3.0	EC002040
ETIM 4.0	EC002040
ETIM 6.0	EC000032
ETIM 7.0	EC000032

UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502
UNSPSC 18.0	31261502

Sealing cap - PROT-M12 FS-M - 1430488

Classifications

UNSPSC

UNSPSC 19.0	31261502
UNSPSC 20.0	31261502
UNSPSC 21.0	31261500

Phoenix Contact 2022 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)