

Wiring bridge - MPB F400X16/ 1GS - 2818342

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Wiring bridge flexible, diameter 16 mm², with a fork-type cable lug on one side, length: 400 mm

Product Features

- ✓ In combination with other devices in the installation distributor, such as residual current devices and miniature circuit breakers
- ✓ Practical wiring of all common applications
- ✓ For combinations of lightning and surge arresters
- ✓ End covers are used to terminate and insulate individually cut bridges



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	74.7 GRM
Custom tariff number	85444290
Country of origin	Germany

Technical data

Dimensions

Height	400 mm
--------	--------

General

Nominal voltage U_N	750 V
Nominal current I_N	100 A (30 °C)
Standards/regulations	DIN VDE 0281-3
Number of positions	1
Color	black

Wiring bridge - MPB F400X16/ 1GS - 2818342

Classifications

eCl@ss

eCl@ss 4.0	27140299
eCl@ss 4.1	27140299
eCl@ss 5.0	27140202
eCl@ss 5.1	27140202
eCl@ss 6.0	27141140
eCl@ss 7.0	27141140
eCl@ss 8.0	27141140

ETIM

ETIM 2.0	EC000489
ETIM 3.0	EC000489
ETIM 4.0	EC000489
ETIM 5.0	EC000489

UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

Drawings

Wiring bridge - MPB F400X16/ 1GS - 2818342

Catalog photo



Figure may contain other products.

Phoenix Contact 2014 © - all rights reserved
<http://www.phoenixcontact.com>

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)