

Interface module - FLKMS-D37 SUB/B/ZFK3DS/PE - 2295952

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



VARIOFACE module, with spring-cage connection and D-Subminiature socket strip, for mounting on NS 35/7.5 or NS 32, 37-pos.



Key commercial data

| | |
|--------------------------------------|-----------|
| Packing unit | 1 pc |
| Weight per Piece (excluding packing) | 201.0 GRM |
| Custom tariff number | 85369010 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|--------|---------|
| Width | 75 mm |
| Height | 86.8 mm |
| Depth | 70 mm |

Ambient conditions

| | |
|---------------------------------|------------------|
| Ambient temperature (operation) | -20 °C ... 50 °C |
|---------------------------------|------------------|

General

| | |
|---|--|
| Nominal voltage U_N | 25 V AC (60 V DC) |
| Max. current carrying capacity per branch | 2.5 A |
| Number of positions | 37 |
| Status display | No |
| Test voltage | 800 V (50 Hz, 1 min.) |
| Mounting position | any |
| Standards/specifications | Air and creepage distances EN 50178 basic insulation |
| Pollution degree | 2 |

Interface module - FLKMS-D37 SUB/B/ZFK3DS/PE - 2295952

Technical data

General

| | |
|--------------------------|--------|
| Surge voltage category | II |
| Rated surge voltage | 1.2 kV |
| Rated insulation voltage | 125 V |

Connection data for connection 1

| | |
|--|------------------------|
| Connection name | PCB connection |
| Connection in acc. with standard | IEC / EN |
| Connection method | Spring-cage connection |
| Number of positions | 39 |
| Conductor cross section solid min. | 0.2 mm ² |
| Conductor cross section solid max. | 2.5 mm ² |
| Conductor cross section stranded min. | 0.2 mm ² |
| Conductor cross section stranded max. | 1.5 mm ² |
| Conductor cross section AWG/kcmil min. | 24 |
| Conductor cross section AWG/kcmil max | 14 |
| Stripping length | 7 mm |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27250313 |
| eCl@ss 4.1 | 27250313 |
| eCl@ss 5.0 | 27250313 |
| eCl@ss 5.1 | 27250313 |
| eCl@ss 6.0 | 27242608 |
| eCl@ss 7.0 | 27141152 |
| eCl@ss 8.0 | 27141152 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001434 |
| ETIM 3.0 | EC001604 |
| ETIM 4.0 | EC001604 |
| ETIM 5.0 | EC002780 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211824 |
| UNSPSC 7.0901 | 39121421 |
| UNSPSC 11 | 39121421 |

Interface module - FLKMS-D37 SUB/B/ZFK3DS/PE - 2295952

Classifications

UNSPSC

| | |
|--------------|----------|
| UNSPSC 12.01 | 39121421 |
| UNSPSC 13.2 | 39121421 |

Approvals

Approvals


Approvals


UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

UL Recognized 

cUL Recognized 

cULus Recognized 

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)