

## RSC 5-T-B

Order No.: 3214916

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=3214916>

Feed-through terminal block with bolt connection, cross section: 0.1 - 6 mm<sup>2</sup>, AWG: 26 - 10, width 16.3 mm, color: Gray

### Commercial data

|                |                                                                                                      |
|----------------|------------------------------------------------------------------------------------------------------|
| GTIN (EAN)     | <br>4 046356 605830 |
| sales group    | A000                                                                                                 |
| Pack           | 50 pcs.                                                                                              |
| Customs tariff | 85369010                                                                                             |

### Product notes

WEEE/RoHS-compliant since:  
08/02/2010



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Accessories

| Item            | Designation                 | Description                                                                                                                                                                    |
|-----------------|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Assembly</b> |                             |                                                                                                                                                                                |
| 3022218         | CLIPFIX 35                  | Snap-on end bracket, for 35 mm NS 35/7.5 or NS 35/15 DIN rail, can be fitted with Zack strip ZB 8 and ZB 8/27, terminal strip marker KLM 2 and KLM, width: 9.5 mm, color: gray |
| 1201442         | E/UK                        | End clamp, for assembly on NS 32 or NS 35/7.5 DIN rail                                                                                                                         |
| 0801762         | NS 35/ 7,5 CU UNPERF 2000MM | DIN rail, material: Copper, unperforated, height 7.5 mm, width 35 mm, length: 2 m                                                                                              |
| 0801733         | NS 35/ 7,5 PERF 2000MM      | Tragschiene, Material: Stahl verzinkt und dickschichtpassiviert, gelocht, Höhe 7,5 mm, Breite 35 mm, Länge: 2000 mm                                                            |

|         |                            |                                                                                                                                   |
|---------|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| 0801681 | NS 35/ 7,5 UNPERF 2000MM   | DIN rail, material: Steel, unperforated, height 7.5 mm, width 35 mm, length: 2 m                                                  |
| 1201756 | NS 35/15 AL UNPERF 2000MM  | Tragschiene, profil-gezogen, hohe Ausführung, ungelocht 1,5 mm dick, Material: Aluminium, Höhe 15 mm, Breite 35 mm, Länge 2000 mm |
| 1201895 | NS 35/15 CU UNPERF 2000MM  | DIN rail, material: Copper, unperforated, 1.5 mm thick, height 15 mm, width 35 mm, length: 2 m                                    |
| 1201730 | NS 35/15 PERF 2000MM       | Tragschiene, Material: Stahl verzinkt und dickschichtpassiviert, gelocht, Höhe 15 mm, Breite 35 mm, Länge: 2000 mm                |
| 1201714 | NS 35/15 UNPERF 2000MM     | DIN rail, material: Steel, unperforated, height 15 mm, width 35 mm, length: 2 m                                                   |
| 1201798 | NS 35/15-2,3 UNPERF 2000MM | DIN rail, material: Steel, unperforated, 2.3 mm thick, height 15 mm, width 35 mm, length: 2 m                                     |
| 2770215 | TS-KK 3                    | Separating plate, Length: 14 mm, Height: 16 mm, Color: gray                                                                       |

**General**

|         |              |                                                                                                                            |
|---------|--------------|----------------------------------------------------------------------------------------------------------------------------|
| 3058017 | AP RSC       | Cover profile, for covering terminal strips, directly snapped onto RBO... and RSC... terminal blocks. Length supplied: 1 m |
| 3058020 | D-RSC 5      | End cover, Length: 53.3 mm, Width: 2.2 mm, Color: gray                                                                     |
| 3059126 | FB 10-13     | Fixed bridge, Number of positions: 10, Color: silver                                                                       |
| 3059663 | FB 10-13 ISO | Bridge bar isolator, Number of positions: 10, Color: silver                                                                |
| 1205163 | SZK PH2 VDE  | Screwdriver, PH crosshead, VDE insulated, size: PH 2 x 100 mm, 2-component grip, with non-slip grip                        |

**Marking**

|         |                   |                                  |
|---------|-------------------|----------------------------------|
| 0829131 | ZB 13:UNBEDRUCKT  | Markers for 13 mm clamping width |
| 0829133 | ZBF 13:UNBEDRUCKT | Markers for 13 mm clamping width |

**Tools**

|         |                 |                                                                                                    |
|---------|-----------------|----------------------------------------------------------------------------------------------------|
| 1205082 | SZS 1,2X8,0 VDE | Screwdriver, bladed, VDE insulated, size: 1.2 x 8.0 x 175 mm, 2-component grip, with non-slip grip |
|---------|-----------------|----------------------------------------------------------------------------------------------------|

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)