

Fiber optic coupling - FOC-ADAPTER:ST/ST-MM - 1208099

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fiber optic coupling, degree of protection: IP20, number of positions: 1, material: Metal, connection method: Coupling, cable outlet: straight, color: silver/matt

Your advantages

- ✓ High reliability with comprehensive quality assurance measures
- ✓ Optimized precision (stability) with the use of ceramic sleeves
- ✓ Versatile range of applications with an extended temperature range and various mounting options
- ✓ Suitable for use for all multimode classes
- ✓ Future-proof with RoHS 2 conformity



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	2 pc
GTIN	 4 063151 277215
GTIN	4063151277215
Custom tariff number	85367000
Country of origin	China

Technical data

Mechanical characteristics

Connection method	Coupling
Number of slots	1
Insertion/withdrawal cycles	≥ 500
Number of positions	1
Cable outlet	straight

Fiber optic coupling - FOC-ADAPTER:ST/ST-MM - 1208099

Technical data

Mechanical characteristics

Weight	10.1 g
Flammability rating according to UL 94	V0

Ambient conditions

Ambient temperature (operation)	-25 °C ... 70 °C
Ambient temperature (assembly)	-5 °C ... 55 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

Material data

Housing material	Metal
Width	14.7 mm
Height	14.7 mm
Length	29.3 mm

Standards and Regulations

Flame resistance	yes
Resistance to oil	yes
Halogen-free	yes

Classifications

eCl@ss

eCl@ss 10.0.1	27440392
eCl@ss 11.0	27440390
eCl@ss 9.0	27440392

ETIM

ETIM 7.0	EC001121
----------	----------

Approvals

Approvals

Approvals

EAC

Ex Approvals

Fiber optic coupling - FOC-ADAPTER:ST/ST-MM - 1208099

Approvals

Approval details

EAC		B.01687
-----	---	---------

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)