

## Screw connection - WP-GR HF IP69K M16 BK - 3240939

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, metric thread, IP68/69k protection, with strain relief

The figure shows the WP-GR HF IP69K M12 BK version

### Key Commercial Data

|                        |          |
|------------------------|----------|
| Packing unit           | 1 STK    |
| Minimum order quantity | 20 STK   |
| Custom tariff number   | 39174000 |
| Country of origin      | Germany  |

### Technical data

#### Dimensions

|                  |                 |
|------------------|-----------------|
| Width (a)        | 20 mm           |
| Height           | 53 mm           |
| Wrench size      | 18.00 mm        |
| Outside diameter | 13.00 mm        |
| Cable diameter   | 13 mm ... 13 mm |

#### Ambient conditions

|                                 |                   |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 115 °C |
| Degree of protection            | IP68/IP69K        |

#### General

|  |  |
|--|--|
| Color                                  | black                                    |
| Type                                   | With strain relief                       |
|  | Outer thread                             |
| Components                             | free from silicone, halogen, and cadmium |
| Flammability rating according to UL 94 | V0                                       |
| Material                               | PA                                       |

### Standards and Regulations

# Screw connection - WP-GR HF IP69K M16 BK - 3240939

## Technical data

### Standards and Regulations

|  |    |
|--|----|
| Connection in acc. with standard       | UL |
| Flammability rating according to UL 94 | V0 |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141131 |
| eCl@ss 4.1 | 27141131 |
| eCl@ss 5.0 | 27141131 |
| eCl@ss 5.1 | 27141120 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 7.0 | 27141120 |
| eCl@ss 8.0 | 27149109 |
| eCl@ss 9.0 | 27144432 |

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC001178 |
| ETIM 5.0 | EC001178 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211812 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121411 |
| UNSPSC 12.01  | 39121411 |
| UNSPSC 13.2   | 39121411 |

## Approvals

### Approvals

---

#### Approvals

UL Recognized / VDE Zeichengenehmigung / LR

---

#### Ex Approvals

---


## Screw connection - WP-GR HF IP69K M16 BK - 3240939


### Approvals

Approvals submitted

---

#### Approval details

UL Recognized 

VDE Zeichengenehmigung 

LR

### Accessories

#### Accessories

##### Corrugated pipe

Protective hose - WP-PA HF 13,0 BK - 3240681



Polyamide protective hose, inflammability class V0, UV resistant

---

Protective hose - WP-PA HF-HB 13,0 BK - 3240839



Polyamide protective hose, inflammability class HB, UV resistant

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)