

Insulating sleeve - MPS-IH GY - 0201728

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Insulating sleeve, Color: gray

Illustration of color insulating sleeves for MPS metal part

Product Features

- Two-piece test plug for individual plug color combinations
- The test plugs are inserted in the function shaft of terminal blocks from the CLIPLINE complete system or in the test connections provided

Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	 4 017918 099107
Weight per Piece (excluding packing)	0.49 g
Custom tariff number	85472000
Country of origin	Poland

Technical data

Dimensions

Height	15.00 mm
Length	5 mm
Width	5 mm

General

Color	gray
Material	PA
Ambient temperature (operation)	-40 °C ... 125 °C

Standards and Regulations

Insulating sleeve - MPS-IH GY - 0201728

Technical data

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Classifications

eCl@ss

eCl@ss 4.0	27060306
eCl@ss 4.1	27060306
eCl@ss 5.0	27061801
eCl@ss 5.1	27141190
eCl@ss 6.0	27141190
eCl@ss 7.0	27141190
eCl@ss 8.0	27149214

ETIM

ETIM 2.0	EC000899
ETIM 3.0	EC000899
ETIM 4.0	EC000448
ETIM 5.0	EC002848

UNSPSC

UNSPSC 6.01	31251501
UNSPSC 7.0901	31251501
UNSPSC 11	31251501
UNSPSC 12.01	31251501
UNSPSC 13.2	31251501

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Insulating sleeve - MPS-IH GY - 0201728

Approvals

Approval details

EAC

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact \(菲尼克斯\)](#)