

Connector hood - SACB-PT-H180- 8/3-M8 HD



1197657

<https://www.phoenixcontact.com/us/products/1197657>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Connector hood, application: Standard, connection method: M8 socket Metal, number of slots: 8, number of positions: 3, slot assignment: single, status display: No, Universal; master cable connection: Plug-in push-in spring-cage connection 180°, shielding: no

Your advantages

- Flexible, distributed bundling of signals in one master cable

Commercial Data

Item number	1197657
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	B08
Product Key	BF3BCG
GTIN	4063151256876
Weight per Piece (including packing)	72.04 g
Weight per Piece (excluding packing)	72.04 g
Customs tariff number	85444290
Country of origin	DE

Connector hood - SACB-PT-H180- 8/3-M8 HD



1197657

<https://www.phoenixcontact.com/us/products/1197657>

Technical Data

Notes

Assembly instruction:

NOTE: Observe the permissible bending radii when laying conductors, since the degree of protection may be put in jeopardy if the bending forces are too high. Alleviate mechanical loads upstream of the connector, e.g. by using cable ties.

Product properties

Product type	Connector hood without master cable
Number of positions	3
Application	Standard
Number of slots	8

Electrical properties

Max. operating voltage U_{max}	30 V DC
Nominal voltage U_N	24 V DC
Rated current, total	8 A
Max. current carrying capacity per path	2 A
Current carrying capacity per slot	2 A

Connection data

Pin assignment

Slot/position = Wire color or connection	1 / 4 (A) = 1 / 4
	2 / 4 (A) = 2 / 4
	3 / 4 (A) = 3 / 4
	4 / 4 (A) = 4 / 4
	5 / 4 (A) = 5 / 4
	6 / 4 (A) = 6 / 4
	7 / 4 (A) = 7 / 4
	8 / 4 (A) = 8 / 4
	1-8 / 1 (+ 24 V) = U_N
	1-8 / 3 (0 V) = 0 V

LED signaling

Status display present	No
------------------------	----

Material specifications

Color	black
Material	PA 6 (Cable gland)
Sealing material	CR/NBR (Cable gland)
Material of contact, master cable side	CU alloy
Material of the contact carrier on the master cable side	PA
Material of contact surface, master cable side	tin-plated

Connector hood - SACB-PT-H180- 8/3-M8 HD



1197657

<https://www.phoenixcontact.com/us/products/1197657>

Housing material	PBT
------------------	-----

Cable / line

Sensor/actuator connection system	M8 socket
Connection method	Plug-in push-in spring-cage connection
Metric conductor cross section (Signal)	0.2 mm ² ... 1.5 mm ²
Cross section AWG (Signal)	24 ... 16
Stripping length (signal)	10 mm
Metric conductor cross section (Power)	0.2 mm ² ... 1.5 mm ²
Cross section AWG (Power)	24 ... 16
Stripping length for sheath	70 mm (Master cable)
Tightening torque, cover screw	1 Nm

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-25 °C ... 80 °C


Connector hood - SACB-PT-H180- 8/3-M8 HD

1197657

<https://www.phoenixcontact.com/us/products/1197657>



Drawings




Connector hood - SACB-PT-H180- 8/3-M8 HD

1197657

<https://www.phoenixcontact.com/us/products/1197657>

Schematic diagram



PCB connector positioning - the UN connection is on the end of the connector hood opposite the cable gland

Connector hood - SACB-PT-H180- 8/3-M8 HD



1197657

<https://www.phoenixcontact.com/us/products/1197657>

Classifications

ECLASS

ECLASS-9.0	27440108
ECLASS-10.0.1	27440111
ECLASS-11.0	27440111

ETIM

ETIM 8.0	EC003558
----------	----------

UNSPSC

UNSPSC 21.0	31251500
-------------	----------

Connector hood - SACB-PT-H180- 8/3-M8 HD



1197657

<https://www.phoenixcontact.com/us/products/1197657>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Connector hood - SACB-PT-H180- 8/3-M8 HD



1197657

<https://www.phoenixcontact.com/us/products/1197657>

Mandatory Accessories

Sensor/actuator box header

Sensor/actuator box header - SACB- 8/3-L-C-M8 HD GG - 1197612

<https://www.phoenixcontact.com/us/products/1197612>



Sensor/actuator box header, application: Standard, connection method: M8 socket Metal, number of slots: 8, number of positions: 3, coding: A - standard, slot assignment: single, status display: yes, pnp; master cable connection: Plug-in master cable connection, shielding: no

Accessories

Master cable ring

Master cable ring - SACB- 8X0,34/2X0,75-50 PUR - 1517592

<https://www.phoenixcontact.com/us/products/1517592>



Master cable for sensor/actuator boxes, without PE conductor, unshielded, material PUR/PVC, 10-pos., 8 x 0.34 mm² and 2 x 0.75 mm², length: 50 m

Connector hood - SACB-PT-H180- 8/3-M8 HD



1197657

<https://www.phoenixcontact.com/us/products/1197657>

Torque screwdriver

Torque screwdriver - TSD 25 SAC - 1212315

<https://www.phoenixcontact.com/us/products/1212315>



Torque screwdriver, with preset torque of 2.5 Nm and 4 mm hexagonal drive for the pressure nut of the connector hood

Tool

Tool - SAC BIT HOOD-W 24 - 1212486

<https://www.phoenixcontact.com/us/products/1212486>



Nut for assembling pressure nuts with 24 mm wrench size, for 4 mm hexagonal drive

Connector hood - SACB-PT-H180- 8/3-M8 HD



1197657

<https://www.phoenixcontact.com/us/products/1197657>

Screwdriver

Screwdriver - SZK PZ2 VDE - 1206463

<https://www.phoenixcontact.com/us/products/1206463>



Screwdriver, PZ crosshead, VDE insulated, size: PZ 2 x 100 mm, 2-component grip, with non-slip grip

Marker for terminal blocks

Marker for terminal blocks - UCT1U-TM 5 - 0803204

<https://www.phoenixcontact.com/us/products/0803204>



UniCard materials for thermal transfer printers, for marking terminal blocks from Weidmüller, Conta Clip, and Klemsan, 72-section, offset foot, can be marked with THERMOMARK CARD and BLUEMARK, color: white

Connector hood - SACB-PT-H180- 8/3-M8 HD



1197657

<https://www.phoenixcontact.com/us/products/1197657>

Marker for terminal blocks

Marker for terminal blocks - UCT1U-TM 5 CUS - 8191012

<https://www.phoenixcontact.com/us/products/8191012>



Markers for terminal blocks, for marking terminal blocks from Weidmüller, Conta Clip, and Klemsan, 72-section, offset foot, can be ordered in sheet form, marked according to customer specifications, color: white

Marker for terminal blocks

Marker for terminal blocks - UCT1-TMF 5 - 0829237

<https://www.phoenixcontact.com/us/products/0829237>



UniCard materials for thermal transfer printers, for labeling Weidmüller, Conta Clip, and Klemsan terminal blocks with horizontal marker groove, 72-section, can be labeled with THERMOMARK CARD and BLUEMARK LED, color: white

Connector hood - SACB-PT-H180- 8/3-M8 HD



1197657

<https://www.phoenixcontact.com/us/products/1197657>

Marker for terminal blocks

Marker for terminal blocks - UCT1-TMF 5 CUS - 0829718

<https://www.phoenixcontact.com/us/products/0829718>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 5.2 mm, lettering field size: 4.45 x 5.2 mm, Number of individual labels: 72

Screwdriver

Screwdriver - SZS 0,4X2,5 VDE - 1205037

<https://www.phoenixcontact.com/us/products/1205037>



Screwdriver, slot-headed, VDE insulated, size: 0.4 x 2.5 x 80 mm, 2-component grip, with non-slip grip

Connector hood - SACB-PT-H180- 8/3-M8 HD



1197657

<https://www.phoenixcontact.com/us/products/1197657>

Screw insert

Screw insert - SF-BIT-SL 0,45X2,4-70 - 1212607

<https://www.phoenixcontact.com/us/products/1212607>



Screw bit, slotted, E6.3-1/4" drive, size: 0.45 x 2.4 x 70 mm, hardened, suitable for holder according to DIN 3126-F6.3/ISO 1173

Screwdriver

Screwdriver - SF-M BH - 1212070

<https://www.phoenixcontact.com/us/products/1212070>



Bit screwdriver, with 1/4" quick-action chuck, handle length 119 mm, 2-component handle, with non-slip grip, suitable for bits according to DIN 3126-C 6.3 and E 6.3/ISO 1173, magnetic

Phoenix Contact 2022 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)