

## Speed starter - CSS 0.37-3/3 - 1201683

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Speed starter with soft start and configurable speed for starting and reversing motors up to 480 V AC and 0.37 kW, configurable motor protection, STO function up to SIL 3 / PL e, Push-in connection, three-phase load input

**RoHS**

### Key Commercial Data

|                      |                                                                                                         |
|----------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit         | 1 pc                                                                                                    |
| GTIN                 | <br>4 063151 265380 |
| GTIN                 | 4063151265380                                                                                           |
| Custom tariff number | 85371098                                                                                                |
| Country of origin    | Taiwan                                                                                                  |

### Technical data

#### Dimensions

|        |                                                          |
|--------|----------------------------------------------------------|
| Width  | 35 mm                                                    |
| Height | 210 mm                                                   |
| Depth  | 174.7 mm                                                 |
| Length | ≤ 50 m (Motor cable length (EMC compliance category C2)) |
|        | ≤ 50 m (Motor cable length (EMC compliance category C3)) |
|        | ≤ 50 m (Motor cable length (no EMC compliance))          |

#### Ambient conditions

|                                         |                                                 |
|-----------------------------------------|-------------------------------------------------|
| Ambient temperature (operation)         | -20 °C ... 55 °C (without current derating)     |
|                                         | -20 °C ... 60 °C (with linear current derating) |
| Ambient temperature (storage/transport) | -25 °C ... 85 °C                                |
| Maximum altitude                        | ≤ 2000 m                                        |

## Speed starter - CSS 0.37-3/3 - 1201683

### Technical data

#### Ambient conditions

|                                          |                          |
|------------------------------------------|--------------------------|
|                                          | > 2000 m (with derating) |
| Permissible humidity (operation)         | 90 % (non-condensing)    |
| Permissible humidity (storage/transport) | 95 % (non-condensing)    |
| Degree of protection                     | IP20                     |
|                                          | NEMA 1                   |
| Vibration (operation)                    | 0,075 mm / 1g            |
| Shock (operation)                        | 15g, 11 ms               |

#### Input

|                     |                                       |
|---------------------|---------------------------------------|
| Designation         | Mains                                 |
| Number of phases    | 3                                     |
| Input voltage       | 380 V AC                              |
|                     | 400 V AC                              |
|                     | 480 V AC                              |
| Input voltage range | 220 V AC ... 480 V AC -15 % ... +10 % |
| Frequency range     | 47 Hz ... 63 Hz                       |
| Nominal current     | 1.7 A (no line reactor)               |
|                     | 1.5 A (with line reactor)             |

#### Output

|                                  |                                              |
|----------------------------------|----------------------------------------------|
| Nominal motor power              | 0.37 W                                       |
| Apparent power                   | 1 kVA                                        |
| Nominal output current ( $I_N$ ) | 1.5 A (4 kHz)                                |
|                                  | 1.1 A (8 kHz)                                |
|                                  | 0.6 A (16 kHz)                               |
| Output frequency                 | 0 Hz ... 500 Hz                              |
| Power dissipation                | 17 W (2 kHz)                                 |
|                                  | 22 W (4 kHz)                                 |
|                                  | 21 W (8 kHz)                                 |
|                                  | 20 W (16 kHz)                                |
|                                  | 9 W (stand by)                               |
| Output current                   | $\leq 2.25$ A (180 s)                        |
|                                  | $\leq 1.125$ A (180 s, during recovery time) |
|                                  | $\leq 2.7$ A (15 s)                          |
|                                  | $\leq 0.75$ A (15 s, during recovery time)   |
| Recovery time                    | 150 s (180 s)                                |
|                                  | 12 s (15 s)                                  |
| Overload time                    | 30 s (180 s)                                 |

# Speed starter - CSS 0.37-3/3 - 1201683

## Technical data

### Output

|                |                                          |
|----------------|------------------------------------------|
|                | 3 s (15 s)                               |
| Discharge time | 3 min. (Intermediate circuit capacitors) |

### General

|                    |          |
|--------------------|----------|
| Cooling            | Heatsink |
| EMC filter present | No       |
| Number of phases   | 3        |

### Standards and Regulations

|                       |               |
|-----------------------|---------------|
| Standards/regulations | IEC 61800-5-1 |
|                       | IEC 61800-3   |
| Pollution degree      | 2             |
| Vibration (operation) | 0,075 mm / 1g |
| Shock (operation)     | 15g, 11 ms    |

### Conformance/approvals

|                |                                             |
|----------------|---------------------------------------------|
| Designation    | Safety Integrity Level (SIL, IEC 61800-5-2) |
| Identification | 3                                           |
| Designation    | Performance Level (EN ISO 13849)            |
| Identification | e                                           |

### Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| China RoHS | Environmentally Friendly Use Period = 25;                                                           |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

## Classifications

### eCl@ss

|             |          |
|-------------|----------|
| eCl@ss 9.0  | 27142320 |
| eCl@ss 11.0 | 27142320 |

## Approvals

### Approvals

### Approvals

UL Listed / cUL Listed / cULus Listed

# Speed starter - CSS 0.37-3/3 - 1201683

## Approvals

Ex Approvals

### Approval details

|              |                                                                                   |                                                                                                                                                         |               |
|--------------|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| UL Listed    |  | <a href="http://database.ul.com/cgi-bin/XYVV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYVV/template/LISEXT/1FRAME/index.htm</a> | FILE E 322526 |
| cUL Listed   |  | <a href="http://database.ul.com/cgi-bin/XYVV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYVV/template/LISEXT/1FRAME/index.htm</a> | FILE E 322526 |
| cULus Listed |  |                                                                                                                                                         |               |

## Accessories

### Accessories

#### Assembly adapter

Power distribution board - EM-CPS-225 - 1002634



Modular power distribution board with CrossLink® interface, 125 A, 3-pos., touch-proof and protection against polarity reversal, width: 225 mm

Power distribution board - EM-CPS-405 - 1002635



Modular power distribution board with CrossLink® interface, 125 A, 3-pos., touch-proof and protection against polarity reversal, width: 405 mm

## Speed starter - CSS 0.37-3/3 - 1201683

### Accessories

Connection module - EM-CPS-TB3/63A - 1002633



Connection module with integrated spring-loaded terminals for cables from 1.5 to 16 mm<sup>2</sup>, 3-pos., maximum 63 A

---

Connection module - EM-CPS-TB3/125A - 1070299



Connection module with box terminals for conductors from 6 to 50 mm<sup>2</sup>, 3-pos., maximum 125 A

---

### Shroud

Shield connection - EM-CSS-MOTORSHIELD-35 - 1276914



Shroud for motor lines for 35 mm CONTACTRON Speed Starters

---

Shield connection - EM-CSS-CONTROLSHIELD-35 - 1276904



Shroud for control lines for 35 mm wide CONTACTRON Speed Starters

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)