

DIN rail - NS 32 CU/120QMM UNPERF 2000MM - 1201280


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



G-profile DIN rail, deep-drawn, material: Copper, unperforated, height 15 mm, width 32 mm, length 2 m



Key commercial data

Packing unit	1 m
Minimum order quantity	5 m
GTIN	 4 017918 017255
Weight per Piece (excluding packing)	2175.0 GRM
Custom tariff number	74072190
Country of origin	Switzerland

Technical data

Dimensions

Height	15 mm
Length	2000 mm
Width	32 mm

General

Material	Copper
Coating	uncoated
Color	copper-colored
Test standard	Similar to EN 60715

DIN rail - NS 32 CU/120QMM UNPERF 2000MM - 1201280

Classifications

eCl@ss

eCl@ss 4.0	23150301
eCl@ss 4.1	23150301
eCl@ss 5.0	27141143
eCl@ss 5.1	27141143
eCl@ss 6.0	27141143
eCl@ss 7.0	27141143
eCl@ss 8.0	27141143

ETIM

ETIM 2.0	EC001285
ETIM 3.0	EC001285
ETIM 4.0	EC001285
ETIM 5.0	EC001285


UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	39121708
UNSPSC 11	39121708
UNSPSC 12.01	39121708
UNSPSC 13.2	39121708

Drawings

DIN rail - NS 32 CU/120QMM UNPERF 2000MM - 1201280

Dimensioned drawing



单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)