

# CABLE-FLK20/OE/0,14/ 200


Order No.: 2305321

The illustration shows a 50-pos. version



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2305321>

Round cable assembled with a 20-pos. socket strip and an open end. On the open end, the wires are labeled with 1 to 20 and have ferrules, cable length: 2 m

| Commercial data          |   |
|--------------------------|---|
| GTIN (EAN)               |  |
| sales group              | I680  |
| Pack                     | 1 pcs.  |
| Customs tariff           | 85444290  |
| Catalog page information | Page 261 (IF-2009)  |

### Product notes

WEEE/RoHS-compliant since: 12/20/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

| Technical data                          |                  |
|---|------------------|
| <b>General</b>                          |                  |
| Nominal voltage $U_N$                   | < 50 V AC        |
|   | 60 V DC          |
| Max. current carrying capacity per path | 1 A              |
| Max. conductor resistance               | 0.16 $\Omega$ /m |

|   |   |
|---|---|
| Ambient temperature (operation)               | -20 °C ... 50 °C                                    |
| Ambient temperature (storage/transport)       | -20 °C ... 70 °C                                    |
| Number of positions                           | 20  |
| Number of positions, control side             | 20  |
| Number of connectors, control side            | 0   |
| Number of positions, module side              | 20  |
| Number of connectors, modul side              | 1   |
| Fixed cable length                            | 2 m   |
| Single wire, cross section                    | 0.14 mm <sup>2</sup>                                |
| AWG   | 26  |
| Conductor construction: Number of litz wires: | 7   |
| Single wire, material                         | Cu tin-plated                                       |
| Test voltage                                  | 0.8 kV  |
| External diameter                             | 7.6 mm  |
| Cable, preassembly                            | Insulation displacement, IEC 60352-4/DIN EN 60352-4 |
| Shielding                                     | no  |

#### Certificates / Approvals



Certification

CUL, UL

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact  
Technical modifications reserved;

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact \(菲尼克斯\)](#)