

FO cable - FL FOC PN-B-980/1000 - 2313397

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



PROFINET polymer fiber cable, duplex, 980/1000 µm, heavy-weight design, for permanent indoor installation, by the meter, without connector

Product Features

- ✓ Universal installation cable for fixed installation indoors
- ✓ 2.2 mm individual wires made from extremely hard-wearing polyamide (PA)
- ✓ Rugged polyurethane (PUR) outer sheath
- ✓ PROFINET type B
- ✓ Halogen-free, ozone, and UV resistant
- ✓



Ethernet



Key commercial data

Packing unit	1 pc
Custom tariff number	85447000
Country of origin	Germany

Technical data

Mechanical characteristics

Number of positions	2
Fiber	Polymer fiber, 980/1000 µm
Cable diameter	8 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 70 °C
	-20 °C ... 70 °C (with quick mounting connector)
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	5000 m

Material data

FO cable - FL FOC PN-B-980/1000 - 2313397

Technical data

Material data

Outer sheath, material	PUR
External sheath, color	Green

Electrical characteristics

Number of positions	2
---------------------	---

Line characteristics

Cable abbreviation	J-V11Y 4Y2P 980/1000 160A 10
Length of cable	Free input (0.4 ... 100 m)
External cable diameter	8 mm
Wire colors	Black and orange with arrow labeling
External sheath, color	Green
Outer sheath, material	PUR
Strain relief elements, external sheath	Non-metallic, aramide fiber
Cable weight	49 kg/km
Bending radius, single element	30 mm (Short-term)
	30 mm (Permanent)
Bending radius, entire cable	65 mm (Short-term)
	65 mm (Permanent)
Tensile strength short-term/long-term	1000 N / 100 N
Lateral pressure short term	200 N/cm
Lateral pressure, long-term	20 N/cm
Impact strength	2 Nm / 10 x
cable layer type	Indoors
Halogen-free	According to IEC 60754-2
Resistance to oil	IRM 902 No.2, 100 °C, DIN VDE 0473-811-2-1

Ambient conditions

Ambient temperature (operation)	-20 °C ... 70 °C
	-20 °C ... 70 °C (with quick mounting connector)
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	5000 m

Attenuation

660 nm	230 dB/km
--------	-----------

FO cable - FL FOC PN-B-980/1000 - 2313397

Classifications

eCl@ss

eCl@ss 4.0	27061001
eCl@ss 4.1	27061001
eCl@ss 5.0	27061803
eCl@ss 5.1	27061803
eCl@ss 6.0	27061803
eCl@ss 7.0	27061803
eCl@ss 8.0	27061803

ETIM

ETIM 2.0	EC000034
ETIM 3.0	EC000034
ETIM 4.0	EC000034
ETIM 5.0	EC000034

UNSPSC

UNSPSC 6.01	26121607
UNSPSC 7.0901	26121607
UNSPSC 11	26121607
UNSPSC 12.01	26121607
UNSPSC 13.2	26121607

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)