

## Contact insert - RC-17S1N120000 - 1601799

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Contact insert, number of positions: 17, type of contact: Socket, Solder connection

The figure shows the 12-pos.  
product version



### Key Commercial Data

|                        |                                                                                                         |
|------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit           | 10 pc                                                                                                   |
| Minimum order quantity | 10 pc                                                                                                   |
| GTIN                   | <br>4 046356 236621 |
| GTIN                   | 4046356236621                                                                                           |

### Technical data

#### General

|                                                    |                      |
|----------------------------------------------------|----------------------|
| Insertion/withdrawal cycles mechanical             | 50                   |
| Direction of rotation of contact chamber numbering | Standard             |
| Coding                                             | N                    |
| Contact connection method                          | Solder connection    |
| Type of contacts                                   | Socket               |
| Number of positions                                | 17                   |
| Contact diameter of power contacts                 | 1 mm                 |
| Litz wire cross section of power contacts min.     | 0.08 mm <sup>2</sup> |
| Litz wire cross section of power contacts max.     | 1 mm <sup>2</sup>    |
| Rated current for power contacts                   | 8 A                  |

#### Material

|                    |                             |
|--------------------|-----------------------------|
| Insulator material | PBT                         |
| Contact material   | CuZn                        |
| Contact surface    | Nickel-plated, gold coating |

# Contact insert - RC-17S1N120000 - 1601799

## Technical data

Specifications according to DIN EN 61984:2001

|                                               |         |
|-----------------------------------------------|---------|
| Nominal / operating voltage of power contacts | 48 V AC |
|                                               | 74 V DC |
| Rated surge voltage of power contacts         | 1.5 kV  |
| Overvoltage category of power contacts        | III     |
| Degree of pollution of power contacts         | 3       |

## Environmental Product Compliance


|            |                                                                                                              |
|------------|--------------------------------------------------------------------------------------------------------------|
| REACH SVHC | Lead 7439-92-1                                                                                               |
| China RoHS | Environmentally Friendly Use Period = 50 years                                                               |
|            | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

## Drawings

Schematic diagram



Schematic diagram



## Classifications

### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27440205 |
| eCl@ss 11.0   | 27440223 |
| eCl@ss 4.0    | 27260700 |
| eCl@ss 4.1    | 27260700 |
| eCl@ss 5.0    | 27260700 |
| eCl@ss 5.1    | 27261200 |
| eCl@ss 6.0    | 27261200 |
| eCl@ss 7.0    | 27440205 |
| eCl@ss 9.0    | 27440205 |

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC001121 |
| ETIM 6.0 | EC000438 |
| ETIM 7.0 | EC003557 |

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 6.01 | 43172015 |
|-------------|----------|

## Contact insert - RC-17S1N120000 - 1601799

### Classifications

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11     | 43172015 |
| UNSPSC 12.01  | 43201404 |
| UNSPSC 13.2   | 39121522 |
| UNSPSC 18.0   | 39121522 |
| UNSPSC 19.0   | 39121522 |
| UNSPSC 20.0   | 39121522 |
| UNSPSC 21.0   | 39121400 |

Phoenix Contact 2022 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)