

# Label - US-EML (104X3,8) - 0800464

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Label, Card, white, unlabeled, can be labeled with: THERMOMARK CARD, Mounting type: Adhesive, Lettering field:  $104 \times 3.8 \text{ mm}$ 



The figure shows a similar product

#### **Product Features**

- The US-EML ... and US-EMLC ... UniSheet labeling ranges include markers for marking operating equipment in electrical and system engineering
- The markers, which are supplied in uniform sheets, can be labeled quickly, easily, and cost-effectively using the THERMOMARK CARD
- The UC-EMLC ... labels can be peeled off and stuck back on without disintegrating
- The perforated markers and labels are easy to separate and can be easily fitted
- When used in conjunction with high-quality ink ribbons, they result in a highly resistant form of labeling that is suitable for harsh environments
- ☑ Low restoring forces mean that the labels can even be stuck onto uneven surfaces and edges.

## **Key Commercial Data**

| Packing unit                         | 1 pc     |
|--------------------------------------|----------|
| Minimum order quantity               | 10 pc    |
| Weight per Piece (excluding packing) | 4.8 g    |
| Custom tariff number                 | 39199000 |
| Country of origin                    | Germany  |

#### Technical data

#### **Dimensions**

| Length (b) | 104 mm |
|------------|--------|
| Width (a)  | 3.8 mm |

#### Ambient conditions

| Ambient temperature (operation) | -40 °C 150 °C |
|---------------------------------|---------------|

#### General

| Color      | white                          |
|------------|--------------------------------|
| Components | free from silicone and halogen |

12/11/2015 Page 1 / 2



# Label - US-EML (104X3,8) - 0800464

## Technical data

#### General

| Material                            | Polyester                   |
|-------------------------------------|-----------------------------|
| Wipe resistance                     | DIN EN 61010-1 (VDE 0411-1) |
| Number of individual labels         | 34                          |
| Number of individual labels per row | 1                           |
| Marking mounting type               | Adhesive                    |

## Standards and Regulations

| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

## Classifications

## eCl@ss

| eCl@ss 4.0 | 24190218 |
|------------|----------|
| eCl@ss 4.1 | 24190218 |
| eCl@ss 5.0 | 27141137 |
| eCl@ss 5.1 | 27141137 |
| eCl@ss 6.0 | 27141137 |
| eCl@ss 7.0 | 27141137 |
| eCl@ss 8.0 | 27149129 |

## **ETIM**

| ETIM 2.0 | EC000761 |
|----------|----------|
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 5.0 | EC001288 |

## UNSPSC

| UNSPSC 6.01   | 30211811 |
|---------------|----------|
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

Phoenix Contact 2015 © - all rights reserved http://www.phoenixcontact.com

## 单击下面可查看定价,库存,交付和生命周期等信息

>>Phoenix Contact(菲尼克斯)