Extract from the online catalog

FLK 50/EZ-DR/FCN40/100/OMR-OUT

Order No.: 2304144

http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2304144

System cable, with a 50-pos. flat-ribbon cable strip and a 40-pos. female connector, cable length: 1 m, for CJ 1: OD 231, OD 261, CS 1, C 200 H: OD 218, OD 219

Product notes

WEEE/RoHS-compliant since: 01/01/2006

http://www.download.phoenixcontact.com
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Commercial data

GTIN (EAN)	4 017918 927356
Note	Made-to-order
sales group	I680
Pack	1 pcs.
Customs tariff	85444290
Catalog page information	Page 203 (IF-2009)

Technical data

General

Nominal voltage U_N	< 50 V AC
	60 V DC
Max. current carrying capacity per path	1 A

Downloaded From Oneyac.com

Max. conductor resistance	0.16 Ω/m
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Number of positions, control side	40
Number of connectors, control side	1
Number of positions, module side	50
Number of connectors, modul side	1
Fixed cable length	1 m
Single wire, cross section	0.14 mm²
AWG	26
Conductor construction: Number of litz wires:	7
Single wire, material	Cu tin-plated
External diameter	10.5 mm
Shielding	no

Certificates / Approvals

Certification	CUL, UL

Downloaded From Oneyac.com

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg,Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
http://www.phoenixcontact.de

© 2011 Phoenix Contact
Technical modifications reserved;

Downloaded From Oneyac.com

单击下面可查看定价，库存，交付和生命周期等信息

>>Phoenix Contact(菲尼克斯)

Downloaded From Oneyac.com