

Test plugs - PRC 3-TC-FS6 8-21 - 1621326

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



PRC test plug, black, 3-pos., 1.5 mm² ... 6 mm²/630 V/35 A, with screw connection, for cables with a diameter of 8 mm ... 21 mm.



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	50 pc
Weight per Piece (excluding packing)	80.0 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

General data

Number of positions	3
Protection class	III
Color	black
Locking type	Snap-in locking
Insertion/withdrawal cycles	2000
Pull-out-force	175 N ± 25 N
Insertion force	30 N ± 10 N

Connection data

Rated current	35 A (with 6 mm² conductor cross section)
Rated voltage (III/2)	690 V
Conductor cross section flexible min.	1.5 mm²
Conductor cross section flexible max.	6 mm²
Conductor cross section solid min.	1.5 mm²
Conductor cross section solid max.	6 mm²

Test plugs - PRC 3-TC-FS6 8-21 - 1621326

Technical data

Connection data

Torque	1 Nm
Type of contact	Screw contacts

Material data

Contact material	Cu
Contact surface material	silver-plated
Contact carrier material	PPE
Material of grip body	PPE
Inflammability class according to UL 94	V0

Classifications

eCl@ss


eCl@ss 5.1	27061801
eCl@ss 6.0	27061801
eCl@ss 8.0	27141148

ETIM


ETIM 4.0	EC002255
ETIM 5.0	EC002555

Drawings

Dimensional drawing



Schematic diagram



Connector pin assignment

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)