


Data sheet

2021-02-23
Product version 00
Document revision 00

Order No.: 1119821

Type: LPT 16/ 5-15,0-ZB

PCB terminal block, Lever Push-in connection



1 Main features



- | | | | |
|---------------------------|--------------------------|------------------------|---------------------|
| • No. of pos. | 5 | • Nominal current | 76 A |
| • Conductor cross section | 16 mm ² | • Nominal voltage | 1000 V |
| • Color | green (6021) | • Connection direction | 0 ° |
| • Pitch | 15 mm | • Type of packaging | packed in cardboard |
| • Connection method | Lever Push-in connection | | |

2 Your advantages

- ✓ Tool-free lever principle enables time-saving connection and release of conductors with/without ferrules
- ✓ Clear lever positions provide reliable feedback on opened or closed clamping spaces
- ✓ Defined contact force ensures that contact remains stable over the long term
- ✓ Time-saving push-in connection when lever is closed
- ✓ Intuitive operation, thanks to a color-coded actuation lever




Make sure you always use the latest documentation.
It can be downloaded at: phoenixcontact.net/product/1119821

1119821 LPT 16/ 5-15,0-ZB**3 Table of contents**

1	Main features.....	1
2	Your advantages	1
3	Table of contents	2
4	3D model in PDF can be activated (Acrobat Reader only)	3
5	General Technical Data	4
6	Conductor connection	5
7	Material properties.....	5
8	Dimensions.....	6
9	Series drawing.....	7
10	Application.....	8
11	Packaging information	8
12	Mechanical tests.....	9
13	Electrical tests	10
14	Current carrying capacity/derating curves	12
15	Environmental and durability tests	13
16	Commercial Data.....	14

1119821 LPT 16/ 5-15,0-ZB

4 3D model in PDF can be activated (Acrobat Reader only)



1119821 LPT 16/ 5-15,0-ZB

5 General Technical Data

5.1 item properties

Order No.	1119821
Type	LPT 16/ 5-15,0-ZB
Product type	PCB terminal block
Range of articles	LPT 16/
Pitch	15 mm
Number of positions	5
Number of levels	1
Number of connections	5
Number of potentials	5
Connection method	Lever Push-in connection
Mounting type	Wave soldering
Connection direction of the conductor to the PCB	0 °
Pin layout	Zigzag pinning W

1119821 LPT 16/ 5-15,0-ZB**6 Conductor connection****6.1 Connection capacity**

Conductor cross section, rigid	0.75 mm ² ... 16 mm ² (Conductor connection with open terminal point)
Conductor cross section, rigid	1.5 mm ² ... 16 mm ² (Push-in connection)
Conductor cross section, multi-stranded	0.75 mm ² ... 16 mm ²
Conductor cross section, flexible	0.75 mm ² ... 25 mm ²
Conductor cross section flexible, with ferrule without plastic sleeve	0.75 mm ² ... 16 mm ²
Conductor cross section flexible, with ferrule with plastic sleeve	0.75 mm ² ... 16 mm ²
2 conductors with the same cross section flexible with TWIN ferrule and plastic sleeve	4 mm ² ... 6 mm ²
Stripping length	18 mm ... 20 mm

6.2 Connection capacity AWG

Conductor cross section AWG	18 ... 4
-----------------------------	----------

7 Material properties**7.1 Material of metal parts**

Note	WEEE/RoHS-compliant, whisker-free acc. to IEC 60068-2-82/JEDEC JESD 201
Contact material	Cu alloy
Terminal point surface	Tin (10 - 16 µm Sn)
Soldering area surface	Tin (10 - 16 µm Sn)
Surface characteristics	Tin-plated


7.2 Material of plastic parts

	Housing	Actuation element
Color	green (6021)	orange (2003)
Insulating material	PA	PA GF
Insulating material group	I	I
CTI according to IEC 60112	600	600
Flammability rating according to UL 94	V0	V0
Glow wire flammability index GWFI according to EN 60695-2-12	850	
Glow wire ignition temperature GWIT according to EN 60695-2-13	775	
Temperature for the ball pressure test according to EN 60695-10-2	125 °C	

1119821 LPT 16/ 5-15,0-ZB**8 Dimensions****8.1 Dimensions for the product**

Length	32 mm
Width	71.9 mm
Height (without solder pin)	36 mm
Total height	39.6 mm
Solder pin [P]	3.6 mm

9 Series drawing



1119821 LPT 16/ 5-15,0-ZB**10 Application****11 Packaging information**

Type of packaging	packed in cardboard
Pieces per package	25

11.1 Temperature limit values

Ambient temperature (storage/transport)	-40 °C ... 70 °C
Ambient temperature (assembly)	-5 °C ... 100 °C
Ambient temperature (operation)	-40 °C ... 105 °C (Depending on the current carrying capacity/derating curve)

1119821 LPT 16/ 5-15,0-ZB**12 Mechanical tests****12.1 Pull-out test**

Specification	IEC 60999-1:1999-11
Result	Test passed
Conductor cross section/conductor type/tractive force actual value	0.75 mm ² / solid / > 30 N
Conductor cross section/conductor type/tractive force actual value	0.75 mm ² / flexible / > 30 N
Conductor cross section/conductor type/tractive force actual value	16 mm ² / solid / > 100 N
Conductor cross section/conductor type/tractive force actual value	25 mm ² / flexible / > 135 N

12.2 Check for damage to conductor or loosening

Specification	IEC 60999-1:1999-11
Result	Test passed

1119821 LPT 16/ 5-15,0-ZB**13 Electrical tests****13.1 Electrical data**

Rated current / conductor cross section	76 A / 16 mm ²
Rated insulation voltage (III/2)	1000 V
Rated surge voltage (III/2)	8 kV
Contact resistance	0.38 mΩ
Degree of pollution	2

13.2 Air and creepage distances

Component	PCB terminal block		
Specification	IEC 60947-7-4:2019-01		
Mains type	unearthed mains		
Insulating material group	I		
Comparative tracking index (IEC 60112:2003-01)	CTI 600		
Rated insulation voltage	1000 V	1000 V	1000 V
Rated surge voltage	8 kV	8 kV	6 kV
Degree of pollution	3	2	2
Overvoltage category	III	III	II
Minimum clearance case A (inhomogeneous field)	8 mm	8 mm	5.5 mm
Minimum value of the creepage path requirement in acc. with table	12.5 mm	8 mm	5.5 mm

13.3 Short-time withstand current test

Specification	IEC 60947-7-4:2019-01
Result	Test passed
Conductor cross section/short-time current	16 mm ² / 360 A

13.4 Aging test (climatic impact and corrosion testing)

Specification	IEC 60947-7-4:2019-01
Result	Test passed
Contact resistance R ₁	0.38 mΩ / 16 mm ²
Test sequence 1: low temperature storage	-40 °C / 2 h
Test sequence 2: heat storage	168 h/105 °C
Test sequence 3: noxious gas storage (ISO 6988)	KFW 0.2 S/1 cycle
Contact resistance R ₂	0.2 mΩ / 16 mm ²
Rated impulse voltage at sea level Voltage waveform ≥ (1.2/50 μs)	9.8 kV
Power-frequency withstand voltage Voltage waveform ≥ (50/60 Hz)	4.2 kV

13.5 Insulation resistance

1119821 LPT 16/ 5-15,0-ZB

Specification	IEC 60512-3-1:2002-02
Result	Test passed
Insulation resistance, neighboring positions	> 5 MΩ

13.6 Mechanical connection test for the PCB terminal block


Specification	IEC 60947-7-4:2019-01
Result	Test passed

13.7 Temperature rise test

Specification	IEC 60947-7-4:2019-01
Result	Test passed
Requirement temperature-rise test	The sum of ambient temperature and temperature rise of the PCB terminal block shall not exceed the upper limiting temperature.
Conductor cross section/test current/temperature rise	16 mm ² / 76 A / 41.7 K
Conductor cross section/test current/temperature rise	10 mm ² / 57 A / 33.7 K
Conductor cross section/test current/temperature rise	6 mm ² / 41 A / 30.2 K

1119821 LPT 16/ 5-15,0-ZB**14 Current carrying capacity/derating curves**

Specification	IEC 60947-7-4:2019-01
Note	Representation based on IEC 60512-5-2:2002-02
Reduction factor	1
Number of positions	4
Conductor cross section	16 mm ²

Type: LPT 16/...-15,0-ZB

1119821 LPT 16/ 5-15,0-ZB**15 Environmental and durability tests****15.1 Vibration test**

Specification	IEC 60068-2-6:2007-12
Result	Test passed
Frequency	10 - 150 - 10 Hz
Sweep speed	1 octave/min
Amplitude	0.35 mm (10 - 60.1 Hz)
Acceleration	50 m/s ² (60.1 - 150 Hz)
Test duration per axis	2.5 h
Test directions	X-, Y- and Z-axis
Note	

15.2 Assessment of fire risk (glow wire test)

Specification	IEC 60695-2-10:2013-04		
Result	Test passed		
Temperature	850 °C		
Time of exposure	5 s		

15.3 Shock protection

Specification	Following IEC 60529:1989-11 + AMD 1:1999-11 + AMD 2:2013-08
Back of the hand protection (Ball ø 50)	conditional guaranteed
Finger protection (movable test finger)	conditional guaranteed
Note	Contact protection above the PCB is only assured when a conductor with a cross-section of 6 mm ² is connected.

1119821 LPT 16/ 5-15,0-ZB**16 Commercial Data**

Order No.	1119821
Type	LPT 16/ 5-15,0-ZB
Pieces per package	25
Net weight	2.22 g
GTIN	4063151065683
	Information that applies locally, see link on page 1
Country of origin	Information that applies locally, see link on page 1

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)