

Crimping pliers - CRIMPFOX-P SR 6 - 1212755

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Crimping pliers, for SUNCLIX solar crimp connectors 2.5 ... 6 mm², unlockable pressure lock, precise parallel crimping, lateral entry, B crimp, incl. positioning tool

Why buy this product

- Precision-manufactured dies ensure consistently high levels of quality during contact processing
- Precision-manufactured dies ensure consistently high levels of quality during contact processing
- High crimping force with low manual force
- Parallel motion sequences of the dies for symmetrical and optimum crimping results
- For stranded class 5 cables according to IEC 60228

Key Commercial Data

Packing unit	1 STK
Custom tariff number	82032000
Country of origin	Sweden

Technical data

General

Color	black
Compression	B crimp
Type of contact	Solar connector
Designation	Crimping position 1
Max. cross section	4 mm ²
AWG max	12
Designation	Crimping position 2
Max. cross section	6 mm ²
AWG max	10
Designation	Crimping position 3
Max. cross section	2.5 mm ²
AWG max	14

Crimping pliers - CRIMPFOX-P SR 6 - 1212755

Classifications

eCl@ss

eCl@ss 5.1	21040301
eCl@ss 6.0	21043811
eCl@ss 8.0	21043706

ETIM

ETIM 4.0	EC002109
ETIM 5.0	EC002109

Accessories

Accessories

Photovoltaic connector

Crimp contact - PV-FT-CCM-2,5-4-R1000 - 1704927



Photovoltaic connector, Nom. voltage: 1500 V, Connection type: Crimp

Crimp contact - PV-FT-CCM-6-R1000 - 1704928



Photovoltaic connector, Nom. voltage: 1500 V, Connection type: Crimp

Crimp contact - PV-FT-CCF-2,5-4-R1000 - 1704930



Photovoltaic connector, Nom. voltage: 1500 V, Connection type: Crimp

Crimping pliers - CRIMPFOX-P SR 6 - 1212755

Accessories

Crimp contact - PV-FT-CCF-6-R1000 - 1704931



Photovoltaic connector, Nom. voltage: 1500 V, Connection type: Crimp

Universal tools

Tool - UNIFOX SR 6 - 1200137



Mounting pliers for snapping the SUNCLIX crimp contacts into the plastic housing, curved 35°, suitable for a conductor diameter of 4.2 mm ... 6.0 mm.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)