

Protective hose - WP-PA HF 10,0 BK - 3240680

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Polyamide protective hose, inflammability class V0, UV resistant

Image shows WP-PA HF 13.0 BK version

Key Commercial Data

Packing unit	1 STK
Minimum order quantity	50 STK
Weight per Piece (excluding packing)	1.000 g
Custom tariff number	39173200
Country of origin	Germany

Technical data

Dimensions

Inner diameter (f)	6.50 mm
Outside diameter	10.00 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 115 °C
Short-term temperature	150 °C

General

Color	black
Type	Helically corrugated plastic hose
Components	free from silicone, halogen, and cadmium
Flammability rating according to UL 94	V0
Material	PA
Bending radius, static	13.00 mm
Bending radius, dynamic	35.00 mm

Standards and Regulations

Resistance to UV radiation	yes
----------------------------	-----

Protective hose - WP-PA HF 10,0 BK - 3240680

Technical data

Standards and Regulations

Halogen-free	yes
Connection in acc. with standard	UL
Flammability rating according to UL 94	V0

Classifications

eCl@ss

eCl@ss 4.0	27141131
eCl@ss 4.1	27141131
eCl@ss 5.0	27141131
eCl@ss 5.1	27141120
eCl@ss 6.0	27141120
eCl@ss 7.0	27141120
eCl@ss 8.0	27430304
eCl@ss 9.0	27430304

ETIM

ETIM 3.0	EC000897
ETIM 4.0	EC001177
ETIM 5.0	EC001177

UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121410
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121411

Approvals

Approvals

Approvals


UL Recognized / VDE Zeichengenehmigung / LR / DNV


Ex Approvals

Protective hose - WP-PA HF 10,0 BK - 3240680

Approvals

Approval details

UL Recognized  <http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm>

VDE Zeichengenehmigung  <http://www.vde.de>

LR <http://www.lr.org/en>

DNV <http://exchange.dnv.com/tari/>

Accessories

Accessories

Corrugated pipe screw connection

Screw connection - WP-G HF IP66 PG7 BK - 3240888



Cable gland, Pg thread, IP66 protection, straight

Screw connection - WP-G HF IP66 M10 BK - 3240895



Cable gland, metric thread, IP66 protection, straight

Screw connection - WP-G HF IP69K PG7 BK - 3240874



Cable gland, Pg thread, IP68/69k protection, straight

Protective hose - WP-PA HF 10,0 BK - 3240680

Accessories

Screw connection - WP-G HF IP69K M10 BK - 3240881



Cable gland, metric thread, IP68/69k protection, straight

Screw connection - WP-GA HF IP66 PG7 BK - 3240916



Cable gland, Pg thread, IP66 protection, angled

Screw connection - WP-GA HF IP66 M10 BK - 3240923



Cable gland, metric thread, IP66 protection, angled

Screw connection - WP-GA HF IP69K PG7 BK - 3240902



Cable gland, Pg thread, IP68/69k protection, angled

Screw connection - WP-GA HF IP69K M10 BK - 3240909



Cable gland, metric thread, IP68/69k protection, angled

Protective hose - WP-PA HF 10,0 BK - 3240680

Accessories

Screw connection - WP-GR HF IP66 PG7 BK - 3240944



Cable gland, Pg thread, IP66 protection, with strain relief

Screw connection - WP-GR HF IP69K PG7 BK - 3240930



Cable gland, Pg thread, IP68/69k protection, with strain relief

Mounting material

Hose holder with cover - WP-BASE C PA HF 10,0 BK - 3240958



Hose holder with cover

Hose clamp - WP-BASE HF 9-10 - 3240965



Hose clamps

Protective cap

Transition sleeve from hose to cable - WP-EC TPE HF 10,0 BK - 3240974



End sleeves, transition sleeves, from hose to cable

Protective hose - WP-PA HF 10,0 BK - 3240680

Accessories

Cable protection end sleeve - WP-SC PA HF 10,0 BK - 3240981



End sleeves as cable protection

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)