

## Front adapters - FLK 50-PA/EZ-DR/HF/KS/ 800/YUC - 2904745

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cast front adapter with attached, halogen-free round cable and a 50-pos. socket strip injection-molded on both sides for the connection of Yokogawa controllers. Cable length: 8.0 m

### Why buy this product

- ☒ Molded connectors
- ☒ KS/AKB-compatible connectors on the module side
- ☒ Can be screwed on
- ☒ Lateral cable outlet of the I/O module

RoHS

### Key Commercial Data

|                      |          |
|----------------------|----------|
| Packing unit         | 1 STK    |
| Custom tariff number | 85444290 |
| Country of origin    | Germany  |

### Technical data

#### Ambient conditions

|                                         |                  |
|-----------------------------------------|------------------|
| Ambient temperature (operation)         | -20 °C ... 70 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

#### General

|                          |                                   |
|--------------------------|-----------------------------------|
| Nominal voltage $U_N$    | 30 V DC                           |
| Max. permissible current | 500 mA (per path at 70°C)         |
| Designation              | Halogen-free sheath               |
| Standards/regulations    | IEC 60754-1                       |
| Designation              | No development of corrosive fumes |
| Standards/regulations    | IEC 60267-2                       |

#### Connection data 1

## Front adapters - FLK 50-PA/EZ-DR/HF/KS/ 800/YUC - 2904745

### Technical data

#### Connection data 1

|                       |                                |
|-----------------------|--------------------------------|
| Connection name       | Control side                   |
| Connection method     | Yokogawa, I/O cards compatible |
| Torque                | 0.5 Nm (Screw connection)      |
| Number of connections | 1                              |
| Number of positions   | 50                             |

#### Connection data 2

|                       |                           |
|-----------------------|---------------------------|
| Connection name       | Field level               |
| Connection method     | Yokogawa, KS compatible   |
| Torque                | 0.5 Nm (Screw connection) |
| Number of connections | 1                         |
| Number of positions   | 50                        |

#### Cable

|                             |                                    |
|-----------------------------|------------------------------------|
| Structural data             | in acc. to UL style 2464/1061      |
| Individual wires per module | 7                                  |
| Single wire, material       | Cu tin-plated                      |
| Single wire, cross section  | 0.14 mm <sup>2</sup>               |
| External diameter           | 11 mm                              |
| Length of cable             | 8 m                                |
| Outer sheath, material      | PVC                                |
| External sheath, color      | gray RAL 7035                      |
| Shielding                   | yes                                |
| Halogen-free cable          | Yes                                |
| Max. conductor resistance   | 0.16 Ω/m                           |
| Cable insulation resistance | approx. 153 MΩ/km                  |
| Cable impedance             | approx. 120 Ω                      |
| Cable resistance            | approx. 155 Ω/km                   |
| Cable capacity              | approx. 130 pF/m                   |
| Insulation                  | Semi-rigid PVC                     |
| Flame resistance            | IEC 60332-3-22                     |
| Resistance to oil           | DIN VDE 0472 Part 803, test type B |
| Gasoline resistance         | Against occasional splashes        |

#### Supported controller

|                     |                          |
|---------------------|--------------------------|
| Controller          | YOKOGAWA CS3000 CentumVP |
| - suitable I/O card | ADV151                   |
|                     | ADV551                   |
| Controller          | YOKOGAWA STARDOM         |

## Front adapters - FLK 50-PA/EZ-DR/HF/KS/ 800/YUC - 2904745

### Technical data

#### Supported controller

|                     |         |
|---------------------|---------|
| - suitable I/O card | NFDV151 |
|                     | NFDV551 |

#### Standards and Regulations

|                       |                                    |
|-----------------------|------------------------------------|
| Resistance to oil     | DIN VDE 0472 Part 803, test type B |
| Flame resistance      | IEC 60332-3-22                     |
| Designation           | Halogen-free sheath                |
| Standards/regulations | IEC 60754-1                        |
| Designation           | No development of corrosive fumes  |
| Standards/regulations | IEC 60267-2                        |

### Drawings

## Front adapters - FLK 50-PA/EZ-DR/HF/KS/ 800/YUC - 2904745

Connection diagram

| 50-pos.<br>connector to<br>the I/O card | 50-pos.<br>connector to<br>the module | Wire color    |
|-----------------------------------------|---------------------------------------|---------------|
| 1                                       | 50                                    | black         |
| 2                                       | 49                                    | brown         |
| 3                                       | 48                                    | red           |
| 4                                       | 47                                    | orange        |
| 5                                       | 46                                    | yellow        |
| 6                                       | 45                                    | green         |
| 7                                       | 44                                    | blue          |
| 8                                       | 43                                    | violet        |
| 9                                       | 42                                    | gray          |
| 10                                      | 41                                    | white         |
| 11                                      | 40                                    | white-black   |
| 12                                      | 39                                    | white-brown   |
| 13                                      | 38                                    | white-red     |
| 14                                      | 37                                    | white-orange  |
| 15                                      | 36                                    | white-yellow  |
| 16                                      | 35                                    | white-green   |
| 17                                      | 34                                    | white-blue    |
| 18                                      | 33                                    | white-violet  |
| 19                                      | 32                                    | white-gray    |
| 20                                      | 31                                    | brown-black   |
| 21                                      | 30                                    | brown-red     |
| 22                                      | 29                                    | brown-orange  |
| 23                                      | 28                                    | brown-yellow  |
| 24                                      | 27                                    | brown-green   |
| 25                                      | 26                                    | brown-blue    |
| 26                                      | 25                                    | brown-violet  |
| 27                                      | 24                                    | brown-gray    |
| 28                                      | 23                                    | brown-white   |
| 29                                      | 22                                    | green-black   |
| 30                                      | 21                                    | green-brown   |
| 31                                      | 20                                    | green-red     |
| 32                                      | 19                                    | green-orange  |
| 33                                      | 18                                    | green-blue    |
| 34                                      | 17                                    | green-violet  |
| 35                                      | 16                                    | green-gray    |
| 36                                      | 15                                    | green-white   |
| 37                                      | 14                                    | yellow-black  |
| 38                                      | 13                                    | yellow-brown  |
| 39                                      | 12                                    | yellow-red    |
| 40                                      | 11                                    | yellow-orange |
| 41                                      | 10                                    | yellow-blue   |
| 42                                      | 9                                     | yellow-violet |
| 43                                      | 8                                     | yellow-gray   |
| 44                                      | 7                                     | yellow-white  |
| 45                                      | 6                                     | gray-black    |
| 46                                      | 5                                     | gray-brown    |
| 47                                      | 4                                     | gray-red      |
| 48                                      | 3                                     | gray-orange   |
| 49                                      | 2                                     | gray-yellow   |
| 50                                      | 1                                     | gray-green    |

## Classifications

eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260704 |
| eCl@ss 7.0 | 27141152 |
| eCl@ss 8.0 | 27249290 |

## Front adapters - FLK 50-PA/EZ-DR/HF/KS/ 800/YUC - 2904745

### Classifications

eCl@ss

|            |          |
|------------|----------|
| eCl@ss 9.0 | 27242292 |
|------------|----------|

ETIM

|          |          |
|----------|----------|
| ETIM 4.0 | EC000237 |
| ETIM 5.0 | EC002584 |

UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211810 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11     | 39121409 |
| UNSPSC 12.01  | 39121409 |
| UNSPSC 13.2   | 39121409 |

### Approvals

Approvals

Approvals

EAC / UL Listed / cUL Listed / cULus Listed

Ex Approvals

Approval details

|                         |
|-------------------------|
| EAC RU C-DE.A*30.B00767 |
|-------------------------|

|                                                                                                                                                                                                                                                                   |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| UL Listed  <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> FILE E 238705 |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                                                                                                                                                                                                                                                                    |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| cUL Listed  <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> FILE E 238705 |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                                                                                                  |
|--------------------------------------------------------------------------------------------------|
| cULus Listed  |
|--------------------------------------------------------------------------------------------------|



单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)