

EMC housing - HC-B 6-TMB-100/O1STM20G-EMV - 1604159

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)

HEAVYCON ADVANCE EMV sleeve housing B6, with bayonet locking, height 100 mm, with 1x M20 thread, straight cable outlet





Key commercial data

Packing unit	1 PCE
Weight per Piece (excluding packing)	308.3 GRM
Custom tariff number	85389099
Country of origin	Germany

Technical data

Dimensions

Height	100 mm
Width	57 mm
Length	92 mm
Length of the assembly cutout	52 mm
Width of the assembly cutout	35 mm

Ambient conditions

Degree of protection of housing (IP)	IP65
	IP67
Ambient temperature (operation)	-40 °C 125 °C

General

Note	For contact inserts HC-B6, BB10, DD24, M
Design	B6
Housing type	Sleeve housings
Locking type	Bayonet locking
Cable exit	Straight

12/6/13 Page 1 / 4



EMC housing - HC-B 6-TMB-100/O1STM20G-EMV - 1604159

Technical data

General

Type of the screw connection	1x M20
Housing material	Aluminum die-cast
Housing surface material	EMC coating, silver
Seal material	NBR, conductive
Material lock	High-grade steel
Material grip body interlock	PA-GF
Assembly instructions	In order to guarantee that the ground conductor contact functions even when plugged in at an angle, the two panel mounting flanges must have sufficient electrical contact with the metal mounting panel.
Connection	If insulating powder coating is present on the control cabinet panel, it should be removed from the profile gasket area in order to ensure optimum shielding.

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27371205
eCl@ss 7.0	27371205
eCl@ss 8.0	27371205

ETIM

ETIM 2.0	EC000437
ETIM 3.0	EC000437
ETIM 4.0	EC000437
ETIM 5.0	EC000437

UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502

Accessories

Accessories



EMC housing - HC-B 6-TMB-100/O1STM20G-EMV - 1604159

Accessories

Panel mounting flange

Mounting flange - HC-B-BF - 1604641



Panel mounting flange for HEAVYCON ADVANCE TMB housing with bayonet locking

Mounting flange - HC-B-BF-SET - 1604654



Bayonet mounting flange set, consisting of 2 mounting flanges with 4 self-tapping Torx® head screws and 4 fan-type spacers

Protective cover


Protective covers - HC-B 6-TMB-SD-IP65 - 1690930




HEAVYCON ADVANCE IP65 protective cover B6, with bayonet locking, with retaining cord, diameter of retaining cord eyelet 3 mm

Drawings


Dimensioned drawing





57

Dimensioned drawing



Mounting cutout ¹⁾ when M4 screws are used ²⁾ when self-tapping Torx® screws are used (Torx® 20, M4)

12/6/13 Page 3 / 4



 $\ensuremath{\mathbb{C}}$ Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com

12/6/13 Page 4 / 4

>>Phoenix Contact(菲尼克斯)