

Cable gland - G-ESIS-M50-L68L-PEPDS-BK - 1415112

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Polyamide, Plastic, Application: Ex, External cable diameter 23 mm ... 35 mm, Shielding: No, Connecting thread: M50, Color: black

The figure shows the G-ESIS-M25-M68L-PEPDS-BK version



Key Commercial Data

Packing unit	1 pc
Custom tariff number	39269097
Country of origin	Germany

Technical data

Dimensions

Length	63 mm
Length without connecting thread	45 mm
Connecting thread diameter	50 mm
Wrench size, union nut	55 mm
Wrench size, support	55 mm
Hexagon angular dimension GRP	61 mm
Length of the connecting thread	18 mm
External cable diameter	23 mm ... 35 mm

Ambient conditions

Degree of protection	IP66
	IP68 (5 bar / 0.5 h)
Ambient temperature (operation)	-40 °C ... 75 °C

General

Cable gland - G-ESIS-M50-L68L-PEPDS-BK - 1415112

Technical data

General

Material	Plastic
Cable gland material	Polyamide
Seal material	EPDM
O-ring material	EPDM
Thread type on connection side	M50
Torque	13 Nm (Support)
Tightening torque, union nut	12.00 Nm
Color	black
ATEX	II 2 G Ex e IIC Gb, II 2 D Ex tb IIIC Db
IECEX	Ex e IIC Gb, Ex tb IIIC Db

Classifications

eCl@ss

eCl@ss 5.1	27149109
eCl@ss 6.0	27149109

ETIM

ETIM 5.0	EC000441
----------	----------

Approvals

Approvals

Approvals

GL

Ex Approvals

ATEX / IECEX / EAC Ex

Approvals submitted


Approval details

Cable gland - G-ESIS-M50-L68L-PEPDS-BK - 1415112

Approvals



Drawings



单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)