

Lightning/surge arrester type 1/2 - VAL-MS-T1/T2 48/12.5/1+0 - 2801241

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Universal varistor-based plug-in lightning/surge arrester for 1-phase power supply networks with common N and PE (2-conductor system: L1, PEN).

Key commercial data

Packing unit	1 pc
Custom tariff number	85363030
Country of origin	Germany

Technical data

Dimensions

Height	90 mm
Width	17.5 mm
Depth	77.5 mm
Horizontal pitch	1 Div.

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 80 °C
Altitude	≤ 2000 m (NN)

General

Housing material	PBT / PA
Inflammability class according to UL 94	V0
Color	black
Standards for air and creepage distances	DIN EN 60664-1
	EN 61643-11
Mounting type	DIN rail: 35 mm
Type	DIN rail module, two-section, divisible
Surge protection fault message	Optical
Direction of action	L-N / L-PEN

Lightning/surge arrester type 1/2 - VAL-MS-T1/T2 48/12.5/1+0 - 2801241

Technical data

Protective circuit

IEC test classification	I / II
	T1 / T2
EN type	T1 / T2
Nominal voltage U_N	60 V AC/DC
	- 48 V DC (RRH)
Maximum continuous operating voltage U_C	75 V AC
	100 V DC
U_T (TOV-proof)	100 V AC (5 s)
	130 V DC (5 s)
Nominal frequency f_N	50 Hz (60 Hz)
Residual current I_{PE}	≤ 0.6 mA
Standby power consumption P_C	≤ 90 mVA
Max. discharge current I_{max} (8/20) μ s	30 kA
Nominal discharge current I_n (8/20) μ s	12.5 kA
Impulse discharge current (10/350) μ s charge	6.25 As
Impulse discharge current (10/350) μ s, specific energy	39 kJ/ Ω
Impulse discharge current (10/350) μ s, peak value I_{imp}	12.5 kA
Voltage protection level U_p	≤ 0.4 kV
Voltage protection level U_p (L+) - (L-)	≤ 0.4 kV
Voltage protection level U_p (L+/L-) - PE	≤ 0.4 kV
Residual voltage	≤ 0.4 kV
	≤ 0.35 kV (at 10 kA)
	≤ 0.3 kV (at 5 kA)
	≤ 0.25 kV (at 3 kA)
Residual voltage (L+) - (L-)	≤ 0.4 kV
Residual voltage (L+/L-) - PE	≤ 0.4 kV
Response time	≤ 25 ns
Max. backup fuse with branch wiring	160 A (gL/gG)
Max. backup fuse with V-type through wiring	80 A (gL / gG)
Short-circuit resistance I_p with max. backup fuse (effective)	25 kA

Connection, protective circuit

Connection method	Screw connection
Connection type IN	Biconnect screw terminal block
Connection type OUT	Biconnect screw terminal block
Connection method	Biconnect terminal block
Screw thread	M5

Lightning/surge arrester type 1/2 - VAL-MS-T1/T2 48/12.5/1+0 - 2801241

Technical data

Connection, protective circuit

Tightening torque	4.5 Nm
	30 lb _F -in. (UL)
Stripping length	16 mm
Conductor cross section stranded min.	1.5 mm ²
Conductor cross section stranded max.	25 mm ²
Conductor cross section solid min.	1.5 mm ²
Conductor cross section solid max.	35 mm ²
Conductor cross section AWG/kcmil min.	15
Conductor cross section AWG/kcmil max.	2
AWG conductor cross section	2 ... 10 (UL)
Tightening torque	30 lb _F -in. (UL)

Standards and Regulations

Standards/regulations	IEC 61643-11 2011
	EN 61643-11 2012
	UL 1449 ed. 3

Classifications

eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130802
eCl@ss 7.0	27130802
eCl@ss 8.0	27130802

ETIM

ETIM 2.0	EC000941
ETIM 3.0	EC000941
ETIM 4.0	EC000381
ETIM 5.0	EC000381

UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610

Lightning/surge arrester type 1/2 - VAL-MS-T1/T2 48/12.5/1+0 - 2801241

Classifications

UNSPSC

UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / KEMA-KEUR / VDE Zeichengenehmigung / CCA / IEC60384-14 / IEC60384-14-1 / IEC60384-14-2 / IEC60384-14-3 / IEC60384-14-4 / IEC60384-14-5 / IEC60384-14-6 / IEC60384-14-7 / IEC60384-14-8 / IEC60384-14-9 / IEC60384-14-10 / IEC60384-14-11 / IEC60384-14-12 / IEC60384-14-13 / IEC60384-14-14 / IEC60384-14-15 / IEC60384-14-16 / IEC60384-14-17 / IEC60384-14-18 / IEC60384-14-19 / IEC60384-14-20 / IEC60384-14-21 / IEC60384-14-22 / IEC60384-14-23 / IEC60384-14-24 / IEC60384-14-25 / IEC60384-14-26 / IEC60384-14-27 / IEC60384-14-28 / IEC60384-14-29 / IEC60384-14-30 / IEC60384-14-31 / IEC60384-14-32 / IEC60384-14-33 / IEC60384-14-34 / IEC60384-14-35 / IEC60384-14-36 / IEC60384-14-37 / IEC60384-14-38 / IEC60384-14-39 / IEC60384-14-40 / IEC60384-14-41 / IEC60384-14-42 / IEC60384-14-43 / IEC60384-14-44 / IEC60384-14-45 / IEC60384-14-46 / IEC60384-14-47 / IEC60384-14-48 / IEC60384-14-49 / IEC60384-14-50 / IEC60384-14-51 / IEC60384-14-52 / IEC60384-14-53 / IEC60384-14-54 / IEC60384-14-55 / IEC60384-14-56 / IEC60384-14-57 / IEC60384-14-58 / IEC60384-14-59 / IEC60384-14-60 / IEC60384-14-61 / IEC60384-14-62 / IEC60384-14-63 / IEC60384-14-64 / IEC60384-14-65 / IEC60384-14-66 / IEC60384-14-67 / IEC60384-14-68 / IEC60384-14-69 / IEC60384-14-70 / IEC60384-14-71 / IEC60384-14-72 / IEC60384-14-73 / IEC60384-14-74 / IEC60384-14-75 / IEC60384-14-76 / IEC60384-14-77 / IEC60384-14-78 / IEC60384-14-79 / IEC60384-14-80 / IEC60384-14-81 / IEC60384-14-82 / IEC60384-14-83 / IEC60384-14-84 / IEC60384-14-85 / IEC60384-14-86 / IEC60384-14-87 / IEC60384-14-88 / IEC60384-14-89 / IEC60384-14-90 / IEC60384-14-91 / IEC60384-14-92 / IEC60384-14-93 / IEC60384-14-94 / IEC60384-14-95 / IEC60384-14-96 / IEC60384-14-97 / IEC60384-14-98 / IEC60384-14-99 / IEC60384-14-100

Ex Approvals

Approvals submitted

Approval details

UL Recognized 

cUL Recognized 

KEMA-KEUR 

VDE Zeichengenehmigung 

CCA

Lightning/surge arrester type 1/2 - VAL-MS-T1/T2 48/12.5/1+0 - 2801241

Approvals

IECEE CB Scheme 

cULus Recognized 

Phoenix Contact 2014 © - all rights reserved
<http://www.phoenixcontact.com>

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)