

# SAC-4P-MS/ 0,3-186/FS SCO

Order No.: 1555680



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1555680>

Sensor/Actuator cable, 4-position, PUR, Black-gray RAL 7021, Plug, straight M12-SPEEDCON, A-coded, on Socket, straight M12-SPEEDCON, A-coded, Cable length: 0.3 m



## Commercial data

|                          |                                                                                                        |
|--------------------------|--------------------------------------------------------------------------------------------------------|
| GTIN (EAN)               | <br>4 046356 173681 |
| Note                     | Made-to-order                                                                                          |
| sales group              | D111                                                                                                   |
| Pack                     | 1 pcs.                                                                                                 |
| Customs tariff           | 85444290                                                                                               |
| Catalog page information | Page 286 (PC-2009)                                                                                     |

## Product notes

WEEE/RoHS-compliant since:  
11/30/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

### General data

|                       |        |
|-----------------------|--------|
| Rated current at 40°C | 4 A    |
| Rated voltage         | 250 V  |
| Number of positions   | 4      |
| Volume resistance     | ≤ 5 mΩ |

|                                 |                                                      |
|---------------------------------|------------------------------------------------------|
| Insulation resistance           | $\geq 100 \text{ M}\Omega$                           |
| Length of cable                 | 0.3 m                                                |
| Ambient temperature (operation) | -25 °C ... 90 °C (Male connector / female connector) |

#### General characteristics

|                          |                                             |
|--------------------------|---------------------------------------------|
| Coding                   | A - standard                                |
| Surge voltage category   | II                                          |
| Pollution degree         | 3                                           |
| Degree of protection     | IP65/IP68/IP69K                             |
| Contact material         | CuSn                                        |
| Contact surface material | Ni/Au                                       |
| Contact carrier material | TPU GF                                      |
| Material of grip body    | TPU, hardly inflammable, self-extinguishing |
| Material, knurls         | Zinc die-cast, (nickel-plated)              |
| Sealing material         | NBR                                         |
| Status display           | No                                          |

#### Conductor data

|                                    |                                             |
|------------------------------------|---------------------------------------------|
| Cable type                         | PUR POWER 0.75 mm <sup>2</sup> black        |
| Cable type (abbreviation)          | 186                                         |
| Cable abbreviation                 | LiY11Y                                      |
| Conductor cross section            | 0.75 mm <sup>2</sup>                        |
| AWG signal line                    | 18                                          |
| Conductor structure signal line    | 42x 0.15 mm                                 |
| Core diameter including insulation | 1.75 mm $\pm$ 0.05 mm                       |
| Thickness, insulation              | $\geq 0.23 \text{ mm}$ (Core insulation)    |
|                                    | $\geq 0.76 \text{ mm}$ (Outer cable sheath) |
| External cable diameter            | 5.90 mm                                     |
| Wire colors                        | Brown, white, blue, black                   |
| External sheath, color             | Black-gray RAL 7021                         |
| Insulation resistance              | $\geq 1 \text{ M}\Omega \cdot \text{km}$    |
| Conductor resistance               | max. 26 $\Omega/\text{km}$                  |
| Nominal voltage, conductor         | $\leq 300 \text{ V}$                        |
| Test voltage, conductor            | $\geq 3000 \text{ V}$                       |
| Overall twist                      | 4 wires, twisted                            |
| Outer sheath, material             | PUR                                         |

|                                               |                                                                                                |
|-----------------------------------------------|------------------------------------------------------------------------------------------------|
| Material conductor insulation                 | PVC                                                                                            |
| Conductor material                            | Bare Cu litz wires                                                                             |
| Cable weight                                  | 57 kg/km                                                                                       |
| Smallest bending radius, movable installation | 59 mm                                                                                          |
| Number of bending cycles                      | 2000000                                                                                        |
| Bending radius                                | 59 mm                                                                                          |
| Traversing path                               | 5 m                                                                                            |
| Traversing rate                               | 3 m/s                                                                                          |
| Acceleration                                  | 5 m/s <sup>2</sup>                                                                             |
| Ambient temperature (operation)               | -25 °C ... 80 °C (cable, fixed installation)<br>-5 °C ... 80 °C (cable, flexible installation) |
| Flame resistance                              | in accordance with DIN UL-Style 20549                                                          |

#### Certificates / Approvals




Certification


CUL Listed, UL Listed

#### Diagrams/Drawings

Dimensioned drawing




M12-SPEEDCON plug, straight



M12-SPEEDCON socket, straight


Circuit diagram




Contact assignment of the M12 plug and the M12 socket

Schematic diagram

---



Pin assignment M12 plug, 4-pos., A-coded, view plug side



Pin assignment M12 socket, 4-pos., A-coded, view female side

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)