

## Profile - UM 108-PROFIL L10,2CM GN VPE50 - 2199320

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Press-drawn section housings, Basic profile, profile width (internal): 122.6 mm, length: 102 mm, color: green (6021)



The figure shows the variant UM 45-Profil CM

### Your advantages

- ✓ Easy installation
- ✓ Flexible size and shape
- ✓ Inexpensive as a result of reducing the number of separate housing parts



### Key Commercial Data

|              |                                                                                      |
|--------------|--------------------------------------------------------------------------------------|
| Packing unit | 50 pc                                                                                |
| GTIN         |  |
| GTIN         | 4046356416788                                                                        |

### Technical data

#### Product properties

|                           |                                |
|---------------------------|--------------------------------|
| Brief article description | Profile                        |
| Type                      | UM 108-PROFIL L10,2CM GN VPE50 |
| Item no.                  | 2199320                        |
| Housing type              | Press-drawn section housings   |
| Housing series            | UM                             |
| Type                      | Basic profile                  |

#### Dimensions

|                          |          |
|--------------------------|----------|
| Length [ l ]             | 102 mm   |
| Profile width (external) | 107.5 mm |
| Profile width (internal) | 122.6 mm |
| Depth [ d ]              | 21.5 mm  |

## Profile - UM 108-PROFIL L10,2CM GN VPE50 - 2199320

### Technical data

#### Material specifications

|                  |              |
|------------------|--------------|
| Housing material | PVC          |
| Color (RAL)      | green (6021) |

#### Ambient conditions

|                                 |                  |
|---------------------------------|------------------|
| Ambient temperature (operation) | -15 °C ... 50 °C |
|---------------------------------|------------------|

#### Packaging specifications

|                            |      |
|----------------------------|------|
| Pieces per package         | 50   |
| Denomination packing units | Pcs. |

#### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

### Classifications

#### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27182701 |
| eCl@ss 11.0   | 27182701 |
| eCl@ss 4.0    | 27180400 |
| eCl@ss 4.1    | 27180400 |
| eCl@ss 5.0    | 27180500 |
| eCl@ss 5.1    | 27180500 |
| eCl@ss 6.0    | 27180800 |
| eCl@ss 7.0    | 27182701 |
| eCl@ss 9.0    | 27182701 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001031 |
| ETIM 4.0 | EC001031 |
| ETIM 6.0 | EC002779 |
| ETIM 7.0 | EC002779 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 31261501 |
| UNSPSC 7.0901 | 31261501 |
| UNSPSC 11     | 31261501 |
| UNSPSC 12.01  | 31261501 |
| UNSPSC 13.2   | 31261501 |
| UNSPSC 18.0   | 31261501 |
| UNSPSC 19.0   | 31261501 |
| UNSPSC 20.0   | 31261501 |
| UNSPSC 21.0   | 31261500 |

---

Phoenix Contact 2022 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)