

Splice box - FOC-FDX20-FR19-STD24-OM1-PT9



1145389

<https://www.phoenixcontact.com/us/products/1145389>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Splice box, type: 19" rack patch module, degree of protection: IP20, material: Sheet steel, connection method: Splicing, housing size: 1, color: light grey RAL 7035



Product Description

FDX 20 series 19" splice boxes, 1 RU, with removable drawer, for 24x ST duplex OM1, metal, completely ready to splice (correctly pre-mounted: 24 ST duplex couplings, 24 filler plugs, 48 pigtails, 4 cassettes, 4 combs, 1 cassette cover).
4 cable entries (rear) incl. 2 Pg16 cable glands, 2 sealing caps, and 19" mounting set.

Commercial Data

Item number	1145389
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	A08
Product Key	ABNAIB
GTIN	4063151135645
Weight per Piece (including packing)	3,502 g
Weight per Piece (excluding packing)	22.22 g
Customs tariff number	85367000
Country of origin	DE

Splice box - FOC-FDX20-FR19-STD24-OM1-PT9



1145389

<https://www.phoenixcontact.com/us/products/1145389>

Technical Data

Product properties

Type	19" rack patch module
Product type	Network distributor box
Connection profile	ST-Duplex
No. of cable outlets	4
No. of conductors	48
Number of module slots	24
Number of slots	48
Type of the screw connection	2x Pg16
Protective cover	yes

Electrical properties

Attenuation	≤ 0.3 dB
-------------	---------------

Connection data

Connection technology

Connection method	Splicing
-------------------	----------

Dimensions

Width	480 mm
Height	44.45 mm
Depth	280 mm

Mechanical characteristics

Ferrule diameter	2.50 mm
------------------	---------

Material specifications

Color	light grey RAL 7035
Flammability rating according to UL 94	V0
Ferrule material	Zirconia ceramics
Housing surface material	Powder-coated, gray
Housing material	Sheet steel

Connector

Insertion/withdrawal cycles	≥ 500
-----------------------------	------------

Cable / line

Cable type	Fiberglass
Cable type	Loose Tube
Cable structure	semi-loose compact wires (STB)
External cable diameter	7 mm ... 12 mm
Individual wire diameter	900 μ m

Splice box - FOC-FDX20-FR19-STD24-OM1-PT9



1145389

<https://www.phoenixcontact.com/us/products/1145389>

Single wire, color	Color coded
Whip length	750 mm
Halogen-free	yes
Flame resistance	yes

FO cable

Number of fibers	48
Fiber	GOF
Fiber type	Multimode fiberglass 62.5/125 µm
Attenuation	≤ 0.3 dB (at 850 nm / 1300 nm)
Return Loss	≥ 35 dB (at 850 nm / 1300 nm)
Transmission medium	FO

Mechanical properties

Mechanical data

Type of the screw connection	2x Pg16
------------------------------	---------

Characteristics

Attenuation	≤ 0.3 dB
-------------	----------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Ambient temperature (assembly)	0 °C ... 50 °C
Resistance to UV radiation	yes

Standards and regulations

Resistance to UV radiation	yes
Flame resistance	yes

Mounting

Mounting type	Screw mounting: M6 x 4
---------------	------------------------

Splice box - FOC-FDX20-FR19-STD24-OM1-PT9



1145389

<https://www.phoenixcontact.com/us/products/1145389>

Approvals



EAC

Approval ID: B.01687

Splice box - FOC-FDX20-FR19-STD24-OM1-PT9



1145389

<https://www.phoenixcontact.com/us/products/1145389>

Classifications

ECLASS

ECLASS-9.0	27440210
ECLASS-10.0.1	19170113
ECLASS-11.0	19170113

ETIM

ETIM 8.0	EC002699
----------	----------

UNSPSC

UNSPSC 21.0	43223300
-------------	----------

Splice box - FOC-FDX20-FR19-STD24-OM1-PT9



1145389

<https://www.phoenixcontact.com/us/products/1145389>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Splice box - FOC-FDX20-FR19-STD24-OM1-PT9



1145389

<https://www.phoenixcontact.com/us/products/1145389>

Mandatory Accessories

Shrink splice protection

Shrink splice protection - FOC-SHRINKSPLICE-PROTECT - 1019676

<https://www.phoenixcontact.com/us/products/1019676>



Shrink splice protection, type: Straight, degree of protection: IP20, cable outlet: above and below, color: transparent

Crimp splice protection

Crimp splice protection - FOC-CRIMPSPLICE-PROTECT - 1019678

<https://www.phoenixcontact.com/us/products/1019678>



Crimp splice protection, type: Straight, degree of protection: IP20, connection method: Crimp connection, cable outlet: above and below, color: Bare metallic

Accessories

Splice box - FOC-FDX20-FR19-STD24-OM1-PT9



1145389

<https://www.phoenixcontact.com/us/products/1145389>

FO patch cable

FO patch cable - FOC-ST:PA-ST:PA-OM1:D01/1 - 1146501

<https://www.phoenixcontact.com/us/products/1146501>

Multi-mode OM1 duplex jumper, ST-ST, UPC polishing, length 1 m




FO patch cable

FO patch cable - FOC-LC:PA-ST:PA-OM1:D01/1 - 1146499

<https://www.phoenixcontact.com/us/products/1146499>

Multi-mode OM1 duplex jumper, LC-ST, UPC polishing, length 1 m



Splice box - FOC-FDX20-FR19-STD24-OM1-PT9



1145389

<https://www.phoenixcontact.com/us/products/1145389>

FO patch cable

FO patch cable - FOC-ST:PA-ST:PA-OM1:D01/2 - 1146509

<https://www.phoenixcontact.com/us/products/1146509>

Multi-mode OM1 duplex jumper, ST-ST, UPC polishing, length 2 m




FO patch cable

FO patch cable - FOC-LC:PA-ST:PA-OM1:D01/2 - 1146508

<https://www.phoenixcontact.com/us/products/1146508>

Multi-mode OM1 duplex jumper, LC-ST, UPC polishing, length 2 m



Splice box - FOC-FDX20-FR19-STD24-OM1-PT9



1145389

<https://www.phoenixcontact.com/us/products/1145389>

FO patch cable

FO patch cable - FOC-ST:PA-ST:PA-OM1:D01/5 - 1146517

<https://www.phoenixcontact.com/us/products/1146517>

Multi-mode OM1 duplex jumper, ST-ST, UPC polishing, length 5 m




FO patch cable

FO patch cable - FOC-LC:PA-ST:PA-OM1:D01/5 - 1146516

<https://www.phoenixcontact.com/us/products/1146516>

Multi-mode OM1 duplex jumper, LC-ST, UPC polishing, length 5 m



Splice box - FOC-FDX20-FR19-STD24-OM1-PT9



1145389

<https://www.phoenixcontact.com/us/products/1145389>

Fiber optic cable

Fiber optic cable - FOC-PT9:SC-OM1/2.5 - 1208107

<https://www.phoenixcontact.com/us/products/1208107>

Fiber optic cable, type: LC, degree of protection: IP20, cable length: 2.5 m, number of positions: 12, connection method: SC, cable outlet: straight, color: beige



Fiber optic cable

Fiber optic cable - FOC-PT9:ST-OM1/2.5 - 1208117

<https://www.phoenixcontact.com/us/products/1208117>

Fiber optic cable, type: ST series, degree of protection: IP20, cable length: 2.5 m, number of positions: 12, connection method: ST, cable outlet: straight, color: silver/glossy



Splice box - FOC-FDX20-FR19-STD24-OM1-PT9




1145389

<https://www.phoenixcontact.com/us/products/1145389>

Fiber optic coupling

Fiber optic coupling - FOC-ADAPTER:SCD/SCD-MM - 1208081

<https://www.phoenixcontact.com/us/products/1208081>



Fiber optic coupling, degree of protection: IP20, number of positions: 2, material: Plastic, connection method: Coupling, cable outlet: straight, color: beige

Fiber optic coupling

Fiber optic coupling - FOC-ADAPTER:STD/SCD-MM - 1208096

<https://www.phoenixcontact.com/us/products/1208096>



Fiber optic coupling, degree of protection: IP20, number of positions: 2, material: Zinc alloy, connection method: Coupling, cable outlet: straight, color: silver/matt

Splice box - FOC-FDX20-FR19-STD24-OM1-PT9



1145389

<https://www.phoenixcontact.com/us/products/1145389>

FO cable

FO cable - FOC-OE-OE-GL-U-OM1-24/... - 1286217

<https://www.phoenixcontact.com/us/products/1286217>



GOF universal cable; 24-wire, loose tube cable for fixed installation; non-metal rodent protection; can be stripped easily; UV resistant; high mechanical and thermal stability; low smoke; halogen-free and self-extinguishing; improved impact resistance; longitudinally and transversely watertight

FO cable

FO cable - FOC-OE-OE-GL-U-OM1-12/... - 1286223

<https://www.phoenixcontact.com/us/products/1286223>



GOF universal cable; 12-wire, loose tube cable for fixed installation; non-metal rodent protection; can be stripped easily; UV resistant; high mechanical and thermal stability; low smoke; halogen-free and self-extinguishing; improved impact resistance; longitudinally and transversely watertight

Phoenix Contact 2022 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)