

Relay connectors - ST-REL3-KG 24/21/AU/SO46 - 2826981

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Pluggable relay interfaces against interference on the control side, with soldered-in miniature switching relays, contacts (Au): small loads, 1 PDT, input voltage 24 V AC/DC

The illustration shows version ST-REL 3-KG 24/21/SO 46

Product Features

- ✓ Use of AC output cards, resulting in residual AC currents
- ✓ Resistant to interference currents
- ✓ Applications with long control lines
- ✓ High relay release voltage



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	44.0 GRM
Custom tariff number	85364190
Country of origin	Germany

Technical data

Dimensions

Width	20.8 mm
Height	42.5 mm
Depth	112 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Coil side

Nominal input voltage U_N	24 V AC
-----------------------------	---------

Relay connectors - ST-REL3-KG 24/21/AU/SO46 - 2826981

Technical data

Coil side

Input voltage range in reference to U_N	0.9 ... 1.1
Typical input current at U_N	26 mA
Typical response time	8 ms (with DC)
Typical release time	10 ms (with DC)
Operating voltage display	Yellow LED
Protective circuit	Bridge rectifier Bridge rectifier
	Surge protection Varistor
	RC element RC element

Contact side

Contact type	Double contact, 1 PDT
Contact material	Au
Maximum switching voltage	30 V AC
	36 V DC
Maximum inrush current	0.2 A
Limiting continuous current	0.5 A
Interrupting rating (ohmic load) max.	5 W

General

Test voltage relay winding/relay contact	2.5 kV AC (50 Hz, 1 min.)
Mechanical service life	Approx. 2×10^7 cycles
Standards/regulations	IEC 60664
	EN 50178
	IEC 62103
Rated surge voltage / insulation	Basic insulation
Pollution degree	2
Surge voltage category	III
Mounting position	any

Classifications

eCl@ss

eCl@ss 4.0	27371104
eCl@ss 4.1	27371104
eCl@ss 5.0	27371001
eCl@ss 5.1	27371001
eCl@ss 6.0	27371001
eCl@ss 7.0	27371001

Relay connectors - ST-REL3-KG 24/21/AU/SO46 - 2826981

Classifications

eCl@ss

eCl@ss 8.0	27371001
------------	----------

ETIM

ETIM 2.0	EC000196
ETIM 3.0	EC000196
ETIM 4.0	EC000196
ETIM 5.0	EC000196

UNSPSC

UNSPSC 6.01	30211916
UNSPSC 7.0901	39121515
UNSPSC 11	39121515
UNSPSC 12.01	39121515
UNSPSC 13.2	39121515

Approvals

Approvals


Approvals


GOST / GOST

Ex Approvals

Approvals submitted

Approval details


GOST 
--

GOST 
--

Relay connectors - ST-REL3-KG 24/21/AU/SO46 - 2826981

Drawings

Circuit diagram



单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)