

## Antenna - FL LCX CABLE METER - 2884774

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



The leaky wave conductor is a "wireless cable" which acts as an antenna and radiates light over the entire length. The range is extremely limited here. Track-guided systems can thus be properly supplied even under rough conditions.

### Key Commercial Data

Packing unit	1 pc
Custom tariff number	85442000
Country of origin	Germany

### Technical data

#### Dimensions

Diameter	13.7 mm
----------	---------

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-70 °C ... 85 °C

#### General

Frequency range	2.4 GHz
	2.4 GHz ... 2.6 GHz
Cable resistance	2.9 Ω/km (DC inner conductor)
	4 Ω/km (DC phase conductor)
Impedance	50 Ω
Gain	0 dBi
Connection method	open end
Cable weight	250.00 g/m
Smallest bending radius, fixed installation	min. 32 mm (One-time bending)
Cable, attenuation	19.8 dB/100 m, longitudinal attenuation (2.4 GHz)
	89 dB, coupling attenuation 95 % (2.4 GHz)
Material	Al Cu wire (inner conductors)
	Copper corrugated tube (Phase conductors)

## Antenna - FL LCX CABLE METER - 2884774

### Technical data

#### General

	PE foam (Insulation)
	Polyethylene (Sheath)
Assembly instructions	Recommended clamp distance 0.33 m

#### Standards and Regulations

Standards/regulations	IEC 60754-1 / -2
	IEC 60332-1 / -3.C

### Classifications

#### eCl@ss

eCl@ss 4.0	240604xx
eCl@ss 4.1	24060401
eCl@ss 5.0	27061804
eCl@ss 5.1	27061804
eCl@ss 6.0	27061804
eCl@ss 7.0	19070105

#### ETIM

ETIM 3.0	EC001698
ETIM 4.0	EC000416
ETIM 5.0	EC001698

#### UNSPSC

UNSPSC 6.01	20142601
UNSPSC 7.0901	20142601
UNSPSC 11	20142601
UNSPSC 12.01	20142601
UNSPSC 13.2	20142601

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)