

## Control cabinet feed-through - CUC-BH-M12A1PBK-A/R4BE - 1414393

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Control cabinet feed-through, M12, 8-pos., A-coded on RJ45 socket, socket input 90°, IP65/67

### Why buy this product

- Compact design
- 1 Gbps
- IP65/67
- UL



**Ethernet Ethernet**

### Key Commercial Data

Packing unit	1 STK
Custom tariff number	85366990
Country of origin	Germany

### Technical data

#### Mechanical characteristics

Shielded	yes
Insertion/withdrawal cycles	≥ 100
Cable exit	angled
Color	black
Mounting type	Rear mounting

#### Ambient conditions

Ambient temperature (operation)	-25 °C ... 85 °C
---------------------------------	------------------

#### Material data

Control cabinet feed-through - CUC-BH-M12A1PBK-A/R4BE - 1414393

Technical data

Material data

Flammability rating according to UL 94	V0
Housing material	PA
Contact material	Copper alloy

Electrical characteristics

Nominal voltage $U_N$	60 V
Nominal current $I_N$	0.5 A
Transmission characteristics (category)	CAT5 (IEC 11801:2002)
GRP transmission properties	Ethernet
Transmission speed	1 Gbps
Rated current	1.75 A

Standards and Regulations


Flammability rating according to UL 94	V0
--	----

Drawings


Explosion  
drawing

Explosion  
drawing

Dimensional drawing



Dimensional drawing



Panel cutout

Classifications

eCl@ss

eCl@ss 8.0	27141134
eCl@ss 9.0	27141134

## Control cabinet feed-through - CUC-BH-M12A1PBK-A/R4BE - 1414393

### Classifications

#### ETIM

ETIM 5.0	EC001283
----------	----------

### Approvals

#### Approvals

#### Approvals


EAC / UL Listed / cUL Listed / EAC / cULus Listed


#### Ex Approvals

#### Approvals submitted

### Approval details

EAC
-----

UL Listed 	
Nominal current I <sub>N</sub>	0.5 A
Nominal voltage U <sub>N</sub>	60 V

cUL Listed 	
Nominal current I <sub>N</sub>	0.5 A
Nominal voltage U <sub>N</sub>	60 V

EAC
-----

## Control cabinet feed-through - CUC-BH-M12A1PBK-A/R4BE - 1414393

### Approvals

cULus Listed 

Phoenix Contact 2016 © - all rights reserved  
<http://www.phoenixcontact.com>

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)