

FO patch cable - FOC-LC:PA-ST:PA-OM2:D01/5




1115584

<https://www.phoenixcontact.com/us/products/1115584>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Multi-mode OM2 duplex jumper, LC-ST, UPC polishing, length 5 m



Your advantages

- Comprehensively tested according to IEC 61753-122-2 and IEC 61753-1 Cat. C
- Temperature change test in accordance with IEC 61300-2-1
- Vibration test according to IEC 61300-2-1
- Tensile strength of the cable connection according to IEC 61300-2-5
- Multimode patch cable with outstanding optical and mechanical properties for indoor installation
- Fire protection with LSZH sheath and UL 94 V0 components
- Interferometer tests at every stage of the certification process
- Satisfies optical and mechanical industry standards
- Connector with UPC polishing for optimum attenuation values

Commercial Data

Item number	1115584
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	A08
Product Key	ABNACF
GTIN	4063151039592
Weight per Piece (including packing)	52.94 g
Weight per Piece (excluding packing)	44 g
Customs tariff number	85447000
Country of origin	CN

Technical Data

Product properties

Product type	Data cable preassembled
Number of positions	2
Connection profile	LC/UPC-ST/UPC connector

Electrical properties

Transmission medium	Multi-mode fiberglass
---------------------	-----------------------

Mechanical properties

Bending radius, long-term	50 mm
Bending radius short term/long term	30 mm
Tensile strength short-term/long-term	70 N

Material specifications

Flammability rating according to UL 94	V0
--	----

Dimensions

External dimensions

External diameter min.	2 mm
External diameter max.	4 mm

Connector

Insertion/withdrawal cycles	≥ 500
-----------------------------	-------

Connection 1

Degree of protection	IP20
----------------------	------

Cable / line

Cable length	5.00 m
Cable weight	5.30 kg/km
Cable abbreviation	I-V(ZN)H
Cable type	Multimode fiberglass
Cable type	Zip cord
Cable structure	Figure 8 cable
External cable diameter	2.00 mm
Outer sheath, material	LSZH
External sheath, color	orange
Single wire, number of litz wires	2
Individual wire diameter	900 µm
Bending radius, long-term	50 mm
Bending radius short term/long term	30 mm
Smallest bending radius, fixed installation	30 mm

FO patch cable - FOC-LC:PA-ST:PA-OM2:D01/5



1115584

<https://www.phoenixcontact.com/us/products/1115584>

Smallest bending radius, movable installation	30 mm
Tensile strength short-term/long-term	70 N
Lateral pressure, long-term	100.00 N/cm
Bending radius, long-term	50 mm
Bending radius short term/long term	30 mm
Smallest bending radius, fixed installation	30 mm
Smallest bending radius, movable installation	30 mm
Halogen-free	complying with IEC 60754-1/2
Resistance to oil	Not resistant to oil, gasoline, acids, and lyes
Concentration of fumes	in accordance with IEC 61034
Flame resistance	yes
Behavior in fire	No corrosive or toxic fumes

FO cable

Number of fibers	2
Fiber	Fiberglass
Fiber type	Multi-mode 50/125 µm fiberglass
Attenuation	≤ 3.5 dB/km (with 850 nm)
Return Loss	≥ 50 dB
Transmission medium	Multi-mode fiberglass

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-20 °C ... 60 °C
Ambient temperature (storage/transport)	-20 °C ... 60 °C
Ambient temperature (assembly)	-20 °C ... 60 °C
Ambient temperature (installation)	-20 °C ... 60 °C
Resistance to oil	Not resistant to oil, gasoline, acids, and lyes

Standards and regulations

Behavior in fire	No corrosive or toxic fumes
Flame resistance	yes
Resistance to oil	Not resistant to oil, gasoline, acids, and lyes
Concentration of fumes	in accordance with IEC 61034
Standards/specifications	IEC 61300-3-4
	RL: IEC 61300-3-6

FO patch cable - FOC-LC:PA-ST:PA-OM2:D01/5



1115584

<https://www.phoenixcontact.com/us/products/1115584>

Approvals



EAC

Approval ID: B.01687

FO patch cable - FOC-LC:PA-ST:PA-OM2:D01/5



1115584

<https://www.phoenixcontact.com/us/products/1115584>

Classifications

ECLASS

ECLASS-9.0	27061003
ECLASS-10.0.1	27061003
ECLASS-11.0	27061003

ETIM

ETIM 8.0	EC002607
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

1115584

<https://www.phoenixcontact.com/us/products/1115584>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2022 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)