

# FLKM 50-PA-SLC500/OUT/2A

Order No.: 2293446



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2293446>

VARIOFACE front adapter, 1 x 16 channels can be connected for Allen-Bradley SLC 500 1746 OA16 and OW16

| Commercial data          |                    |
|--------------------------|--------------------|
| EAN                      | 4017918108847      |
| Pack                     | 1 pcs.             |
| Customs tariff           | 85369010           |
| Weight/Piece             | 0.0586 KG          |
| Catalog page information | Page 192 (IF-2009) |

### Product notes

WEEE/RoHS-compliant since:  
06/04/2007



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

| General                         |  |
|---------------------------------|--|
| Nominal voltage $U_N$           | < 50 V AC  |
|                                 | 60 V DC  |
| Connection type, plug connector | Flat-ribbon cable plug connector in acc. with IEC 60603-13 |
| Number of plug connectors       | 1  |

|   |  |
|---|--|
| No. of positions, plug connector        | 50                                       |
| Number of positions                     | 50                                       |
| Ambient temperature (operation)         | -20 °C ... 50 °C                         |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C                         |
| Mounting position                       | Any                                      |
| Standards/regulations                   | IEC 60664                                |
|   | DIN EN 50178                             |
|   | IEC 62103                                |
| Max. permissible current                | 2 A (per path)                           |
| Max. permissible total current          | 7 A (Per Byte, for supply via connector) |
| Pollution degree                        | 1  |
| Surge voltage category                  | II                                       |
| Supported controller                    | ALLEN-BRADLEY SLC 500                    |
| Supported I/O card                      | 1746 OA16                                |
|   | 1746 OW16                                |


**Certificates / Approvals**



Certification CUL, GOST, UL

**Diagrams/Drawings**

Circuit diagram



Connection scheme FLKM 50-PA-SLC500/OUT/2A

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact  
Technical modifications reserved;

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)