

Current transformer - PACT MCR-V1-21-44- 75-5A-1 - 2277611

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Bus-bar current transformer, 75 A AC primary current; 5 A AC secondary current; accuracy class 1; 2.5 VA rated power



Key commercial data

| | |
|--------------------------------------|-----------|
| Packing unit | 1 pc |
| Weight per Piece (excluding packing) | 200.0 GRM |
| Custom tariff number | 85043129 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|------------------------------------|-------|
| Primary round conductor (diameter) | 21 mm |
| Width | 30 mm |
| Height | 66 mm |
| Depth | 44 mm |
| Width with alternative assembly | 44 mm |
| Height with alternative assembly | 66 mm |
| Depth with alternative assembly | 30 mm |

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -25 °C ... 40 °C |
| Ambient temperature (storage/transport) | -25 °C ... 40 °C |

Input data

| | |
|-------------------------------------|--------------------------|
| Thermal rated short-time current | $I_{th} = 60 * I_n$ |
| Rated surge current | $I_{dyn} = 2.5 * I_{th}$ |
| Rated frequency: Standard converter | 50 Hz ... 60 Hz |
| Surge current limitation factor | FS 5 |

Current transformer - PACT MCR-V1-21-44- 75-5A-1 - 2277611

Technical data

Input data

| | |
|----------------------------------|--------------|
| Rated power | 2.5 VA |
| Primary rated current I_{pn} | 0 A ... 75 A |
| Secondary rated current I_{sn} | 5 A AC |

General

| | |
|---------------------------|------------------------------------|
| Converter type | Tube rod converter |
| Class | 1 |
| Can be calibrated | no |
| Rated insulation voltage | 1 kV |
| Test voltage input/output | 3 kV (50 Hz, 1 min.) |
| Standards/regulations | IEC 60044-1 |
| Color | black |
| Housing material | Polyamide PA fiberglass reinforced |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27210902 |
| eCl@ss 4.1 | 27210902 |
| eCl@ss 5.0 | 27210902 |
| eCl@ss 5.1 | 27210902 |
| eCl@ss 6.0 | 27210902 |
| eCl@ss 7.0 | 27210902 |
| eCl@ss 8.0 | 27210902 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001505 |
| ETIM 3.0 | EC001505 |
| ETIM 4.0 | EC002048 |
| ETIM 5.0 | EC002048 |


UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211501 |
| UNSPSC 7.0901 | 39121019 |
| UNSPSC 11 | 39121006 |
| UNSPSC 12.01 | 39121006 |
| UNSPSC 13.2 | 39121006 |

Current transformer - PACT MCR-V1-21-44- 75-5A-1 - 2277611

Drawings

Dimensioned drawing



Phoenix Contact 2014 © - all rights reserved
<http://www.phoenixcontact.com>

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)