

## Device connector, front mounting - RF-17S2N8AW400 - 1607900

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Device connector, front mounting, straight, Screw locking, M23, Number of positions: 17, Type of contact: Socket, Crimp connection, Axial O-ring, 4xØ2,7, Shielded: Yes

The figure shows the 12-pos. product version with standard contact chamber numbering



### Key commercial data

|                                      |           |
|--------------------------------------|-----------|
| Packing unit                         | 1 pc      |
| Weight per Piece (excluding packing) | 58.96 GRM |
| Custom tariff number                 | 85366990  |
| Country of origin                    | Germany   |

### Technical data

#### General

|  |  |
|--|--|
| Note   | Order information Order crimp contacts Ø 1 mm separately |
| Type of locking                                    | Screw locking  |
| Direction of rotation of contact chamber numbering | Counter direction  |
| Coding   | N  |
| Contact connection method                          | Crimp connection   |
| Type of contacts                                   | Socket   |
| Number of positions                                | 17   |
| Contact diameter of power contacts                 | 1 mm   |
| Nominal current per power contact at 25°C          | 8 A  |
| Mounting type                                      | 4xØ2,7   |

#### Ambient conditions

|                      |                   |
|----------------------|-------------------|
| Ambient temperature  | -20 °C ... 125 °C |
| Degree of protection | IP67              |

## Device connector, front mounting - RF-17S2N8AW400 - 1607900

### Technical data

#### Material

|                            |  |
|----------------------------|--|
| Housing material           | Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn) |
| Insulator material         | PA 66  |
| Gasket and O-ring material | FPM  |

#### Specifications according to DIN EN 61984:2001

|   |        |
|---|--------|
| Installation height max.                      | 2000 m |
| Nominal / operating voltage of power contacts | 100 V  |
| Rated surge voltage of power contacts         | 1.5 kV |
| Surge voltage category of power contacts      | III    |
| Pollution degree of power contacts            | 3      |
| Surge voltage category of signal contacts     | III    |
| Pollution degree of signal contacts           | 3      |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260708 |
| eCl@ss 7.0 | 27440312 |
| eCl@ss 8.0 | 27440312 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC001121 |
| ETIM 5.0 | EC002635 |


#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 43172015 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11     | 43172015 |
| UNSPSC 12.01  | 43201404 |
| UNSPSC 13.2   | 43201404 |


### Drawings

## Device connector, front mounting - RF-17S2N8AW400 - 1607900


Schematic diagram



Dimensioned drawing



Dimensioned drawing



单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)